

# SAFETY DATA SHEET BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

## 1. Identification

**Product identifier** 

Product name BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

Product number MCC-BAC, MCC-BAC101

Synonyms; Common Names "BAC - ISOCLEAN, DEFLUXER"

Recommended use of the chemical and restrictions on use

Restriction on use Cleaning agent.

**Uses advised against**No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier MICROCARE LLC

Manufacturer MICROCARE LLC

595 John Downey Drive New Britain, CT 06051 United States of America

CAGE: OATV9

Tel: +1 800-638-0125, +1 860-827-0626

Fax: +1 860-827-8105 techsupport@microcare.com

**Emergency telephone number** 

Emergency telephone CHEMTREC 1-800-424-9300 (within the U.S.)

+1 703-741-5970 (from anywhere in the world)

## 2. Hazard identification

## Classification of the substance or mixture

Physical hazards Flam. Aerosol 1 - H222 Press. Gas, Compressed - H280

**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Not Classified

**Human health** See Section 11 for additional information on health hazards.

Environmental The product contains volatile organic compounds (VOCs) which have a photochemical ozone

creation potential.

**Physicochemical** The product is highly flammable. Vapours may form explosive mixtures with air. Aerosol

containers can explode when heated, due to excessive pressure build-up.

## Label elements

## BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

## Hazard pictograms







## Signal word

#### Danger

### Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

#### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P314 Get medical advice/ attention if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with national regulations.

## Supplemental label

information

Safety data sheet available on request. For use in industrial installations only.

Contains PROPAN-2-OL

## Other hazards

This product does not contain any substances classified as PBT or vPvB.

## 3. Composition/information on ingredients

#### **Mixtures**

PROPAN-2-OL 60-100% Trade secret

CAS number: 67-63-0

## Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

#### HFC-134a Tetrafluoroethane

10-30%

CAS number: 811-97-2

## Classification

Press. Gas, Liquefied - H280 Simple Asphyxiants - Category 1

The full text for all hazard statements is displayed in Section 16.

## Composition comments

TSCA: The ingredients of this product are on the TSCA Inventory. The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of CFR 1900.1200

## BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

## Composition

#### 4. First-aid measures

## Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical

personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery

position and ensure breathing can take place.

**Ingestion** Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if

the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical

attention if symptoms are severe or persist.

**Skin contact** Rinse with water.

Eye contact Rinse with water. Do not rub eye. Remove any contact lenses and open eyelids wide apart.

Get medical attention if any discomfort continues.

**Protection of first aiders** First aid personnel should wear appropriate protective equipment during any rescue.

## Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

**Inhalation** A single exposure may cause the following adverse effects: Headache. Nausea, vomiting.

Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic

effect.

**Ingestion** Due to the physical nature of this product, it is unlikely that ingestion will occur.

**Skin contact** Repeated exposure may cause skin dryness or cracking.

**Eye contact** Irritating to eyes.

## Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

## 5. Fire-fighting measures

## Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder

or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

## Specific hazards arising from the hazardous product

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and

propellant. Vapours may form explosive mixtures with air.

## BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

Hazardous combustion products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapours.

Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

## 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

**Environmental precautions** 

**Environmental precautions** 

Avoid discharge into drains or watercourses or onto the ground.

## Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

## Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## 7. Handling and storage

## Precautions for safe handling

## BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

## Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

## Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash

contaminated clothing before reuse.

## Conditions for safe storage, including any incompatibilities

**Storage precautions** Store away from incompatible materials (see Section 10). Keep away from oxidizing materials,

heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to

temperatures exceeding 50°C/122°F.

Storage class Chemical storage.

Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

## 8. Exposure controls/Personal protection

## **Control parameters**

## Occupational exposure limits

#### PROPAN-2-OL

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³ Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³

## HFC-134a Tetrafluoroethane

Long-term exposure limit (8-hour TWA): OES 4240 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

#### **Exposure controls**

## Protective equipment





## Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the

product or ingredients.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-

face respirator may be required instead.

**Hand protection** No specific hand protection recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

## BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

Hygiene measures Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke

when using this product.

Respiratory protection Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH

approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Full face mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial

regulation relating to health and safety at work.

Environmental exposure controls

Keep container tightly sealed when not in use.

## 9. Physical and chemical properties

## Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Colourless.

Odour Characteristic. Alcoholic.

Odour threshold Not determined.

Melting point Not applicable.

Initial boiling point and range 82 - 83°C/173 - 174°F @ 101.3 kPa

Flash point 12°C/54°F Method: Tag closed cup.

Upper/lower flammability or

explosive limits

Upper flammable/explosive limit: 12.0 %(V) Lower flammable/explosive limit: 2.0 %(V)

Vapour pressure 41 hPa @ 20°C

Vapour density 1.82

Bulk density 0.785 g/cm3

Solubility(ies) Soluble in water.

**Auto-ignition temperature** 425°C/797°F

Viscosity 2.43 mPa s @ 20°C/70°F

**Explosive properties**The product is flammable. Heating may generate flammable vapours.

**Global Warming Potential** 

(GWP)

Volatility 100%

Volatile organic compound This product contains a maximum VOC content of 785 g/litre.

#### 10. Stability and reactivity

**Reactivity** See the other subsections of this section for further details.

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

## BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

Possibility of hazardous

reactions

The following materials may react strongly with the product: Oxidizing agents.

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurized

container: may burst if heated

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

## 11. Toxicological information

## Information on toxicological effects

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

**Skin sensitization** Based on available data the classification criteria are not met.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable

as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

## BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

**Aspiration hazard** 

**Aspiration hazard** Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

**Inhalation** A single exposure may cause the following adverse effects: Headache. Nausea, vomiting.

Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic

effect.

**Ingestion** Due to the physical nature of this product, it is unlikely that ingestion will occur.

**Skin contact** Repeated exposure may cause skin dryness or cracking.

**Eye contact** Irritating to eyes.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs Central nervous system

Toxicological information on ingredients

PROPAN-2-OL

Carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed.

HFC-134a Tetrafluoroethane

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - inhalation

Acute toxicity inhalation

(LC<sub>50</sub> gases ppmV)

567,000.0

Species Rat

ATE inhalation (gases

ppmV)

567,000.0

Inhalation Vapours irritate the respiratory system. May cause coughing and difficulties in

breathing.

Ingestion May cause stomach pain or vomiting. May cause nausea, headache, dizziness and

intoxication.

Skin contact May cause allergic contact eczema. Contact with liquid form may cause frostbite.

**Eye contact** May cause temporary eye irritation.

12. Ecological information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

**Toxicity** Based on available data the classification criteria are not met.

Ecological information on ingredients

## BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

## PROPAN-2-OL

Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 9,640 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 5102 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

IC<sub>50</sub>, 72 hours: >2,000 mg/l, Algae

HFC-134a Tetrafluoroethane

Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 450 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 980 mg/l, Daphnia magna

Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

**Ecological information on ingredients** 

PROPAN-2-OL

Partition coefficient : 0.05

HFC-134a Tetrafluoroethane

Partition coefficient Pow: 1.06

Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product

residues and hence be potentially hazardous.

**Disposal methods**Do not empty into drains. Empty containers must not be punctured or incinerated because of

the risk of an explosion. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers,

labeled with their contents.

## BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

## 14. Transport information

**DOT transport notes**As supplied, this product is consigned under the Limited Quantities provisions.

**UN number** 

UN No. (IMDG) 1950 UN No. (ICAO) 1950

UN proper shipping name

Proper shipping name (TDG) LIMITED QUANTITY

Proper shipping name (IMDG) UN1950, AEROSOLS, FLAMMABLE, 2.1, LIMITED QUANTITY

Proper shipping name (ICAO) UN1950, AEROSOLS, FLAMMABLE, 2.1, LIMITED QUANTITY

Proper shipping name (DOT) LIMITED QUANTITY

Packing group

Packing group (International) Not applicable.

**Environmental hazards** 

Environmentally hazardous substance/marine pollutant

No.

**Transport in bulk according to** Not applicable. No information required.

Annex II of MARPOL 73/78

and the IBC Code

#### 15. Regulatory information

## Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

## 16. Other information

Classification abbreviations Aerosol = Aerosol

and acronyms

Eye Irrit. = Eye irritation

STOT SE = Specific target organ toxicity-single exposure

**Training advice** Only trained personnel should use this material.

Revision date 2020-09-02

Revision 48

Supersedes date 2019-01-24

SDS number AEROSOL - BAC

SDS status Approved.

Hazard statements in full H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

May displace oxygen and cause rapid suffocation.

## BAC IPA-BASED FLUX REMOVER- ISOCLEAN, AEROSOL

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.