



SAFETY DATA SHEET

VDX DRY LUBRICANT SPRAY, AEROSOL

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

1. Identification

Product identifier

Product name VDX DRY LUBRICANT SPRAY, AEROSOL

Product number MCC-VDX

Recommended use of the chemical and restrictions on use

Restriction on use Lubricant.

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier MICROCARE LLC
Tel: +1 860-827-0626

Emergency telephone number

Emergency telephone INFOTRAC 1-800-535-5053 (CANADA and U.S.A.)
1-352-323-3500 (from anywhere in the world)

2. Hazard identification

Classification of the substance or mixture

WHMIS Regulatory Status This product has been classified according to the hazard criteria of the Hazardous Product Regulations and the SDS contains all required information.

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Label elements

Hazard statements NC Not Classified

Precautionary statements P211 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/ container in accordance with local regulations.

Supplemental label information EUH210 Safety data sheet available on request. RCH001a For use in industrial installations only.

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

VDX DRY LUBRICANT SPRAY, AEROSOL

Mixtures

HFC-134a Tetrafluoroethane	60-100%
CAS number: 811-97-2	
Classification Press. Gas, Liquefied - H280 Simple Asphyxiants - Category 1	
PROPAN-2-OL	1-5% Trade secret
CAS number: 67-63-0	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	
Poly-tfe, omega-hydro-alpha-(methylcyclohexyl)	1-5%
CAS number: 65530-85-0	
Classification Not Classified	

The full text for all hazard statements is displayed in Section 16.

Composition comments TSCA: The ingredients of this product are on the TSCA Inventory. The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of CFR 1900.1200

Composition

4. First-aid measures

Description of first aid measures

General information	If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin contact	Rinse with water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Spray/mists may cause respiratory tract irritation.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.

VDX DRY LUBRICANT SPRAY, AEROSOL

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May be slightly irritating to eyes. May cause discomfort.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the hazardous product

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Risk of explosion.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

VDX DRY LUBRICANT SPRAY, AEROSOL

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F.

Storage class

Chemical storage.

Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.

Usage description

Lubricant.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

HFC-134a Tetrafluoroethane

Long-term exposure limit (8-hour TWA): OES 4240 mg/m³

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³

Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³

A4

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

Exposure controls

VDX DRY LUBRICANT SPRAY, AEROSOL

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

No specific hand protection recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

Respiratory protection

Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Full face mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work.

Environmental exposure controls

Keep container tightly sealed when not in use.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	White/off-white. Waxy solid.
Odour	Slight alcoholic.
Initial boiling point and range	-26.5°C/-15.7°F @ 101.3 kPa
Flash point	The product is not flammable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	The product is not flammable.
Vapour pressure	663 kPa @ 25°C
Vapour density	3.18 @ 25 (C) / 77 (F)
Relative density	No information available.
Solubility(ies)	Slightly soluble in water.
Comments	Aerosol.

VDX DRY LUBRICANT SPRAY, AEROSOL

Global Warming Potential (GWP)

Surface tension

Particle size 1-15 micron

Volatility 98.5%

Heat of vaporization (at boiling point), cal/g (Btu/lb)

10. Stability and reactivity

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurized container: may burst if heated
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

VDX DRY LUBRICANT SPRAY, AEROSOL

Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
<u>General information</u>	
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Spray/mists may cause respiratory tract irritation.
Ingestion	Due to the physical nature of this product, it is unlikely that ingestion will occur.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May be slightly irritating to eyes. May cause discomfort.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target organs	No specific target organs known.

Toxicological information on ingredients

HFC-134a Tetrafluoroethane

Other health effects	There is no evidence that the product can cause cancer.
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ gases ppmV)	567,000.0
Species	Rat
ATE inhalation (gases ppmV)	567,000.0
<u>Inhalation</u>	
Inhalation	Vapours irritate the respiratory system. May cause coughing and difficulties in breathing.
<u>Ingestion</u>	
Ingestion	May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.
<u>Skin contact</u>	
Skin contact	May cause allergic contact eczema. Contact with liquid form may cause frostbite.
<u>Eye contact</u>	
Eye contact	May cause temporary eye irritation.

VDX DRY LUBRICANT SPRAY, AEROSOL

PROPAN-2-OL

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed.

12. Ecological information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

Toxicity Based on available data the classification criteria are not met.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 450 mg/L mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 980 mg/L mg/l, Daphnia magna

Ecological information on ingredients

HFC-134a Tetrafluoroethane

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 450 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 980 mg/l, Daphnia magna

PROPAN-2-OL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 9,640 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 5102 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: >2,000 mg/l, Algae

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Ecological information on ingredients

HFC-134a Tetrafluoroethane

Partition coefficient Pow: 1.06

PROPAN-2-OL

Partition coefficient : 0.05

Mobility in soil

VDX DRY LUBRICANT SPRAY, AEROSOL

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Do not empty into drains. Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents.

14. Transport information

UN number

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN proper shipping name

Proper shipping name (TDG) LIMITED QUANTITY

Proper shipping name (IMDG) UN1950 AEROSOLS, NON-FLAMMABLE, 2.2, LIMITED QUANTITY

Proper shipping name (ICAO) UN1950 AEROSOLS, NON-FLAMMABLE, 2.2, LIMITED QUANTITY

Proper shipping name (DOT) LIMITED QUANTITY

Transport hazard class(es)

IMDG class 2.2 LIMITED QUANTITY

ICAO class/division 2.2 LIMITED QUANTITY

Special precautions for user

Not applicable.

EmS F-C, S-V

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not relevant. No information required.

15. Regulatory information

Inventories

Canada – DSL/NDSL
DSL

VDX DRY LUBRICANT SPRAY, AEROSOL

US - TSCA

Present.

16. Other information

Classification abbreviations and acronyms	Aerosol = Aerosol
Training advice	Only trained personnel should use this material.
Revision date	2021-06-24
Revision	41
Supersedes date	2021-06-03
SDS number	AEROSOL - VDX
SDS status	Approved.
Hazard statements in full	H225 Highly flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. May displace oxygen and cause rapid suffocation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.