

SAFETY DATA SHEET DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK

1. Identification		
Product identifier		
Product name	DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK	
Product number	MCC-DC1L, MCC-DC1G, MCC-DC1P, MCC-DC1D, MCC-DC1GL, MCC-DC1GG	
Synonyms; Common Names	DC1-VERICLEAN FLUX REMOVER, NON AEROSOL	
Recommended use of the chemical and restrictions on use		
Restriction on use	Cleaning agent.	
Details of the supplier of the s	afety data sheet	
Supplier	MICROCARE LLC	
Manufacturer	MICROCARE LLC	
	595 John Downey Drive	
	New Britain, CT 06051	
	United States of America CAGE: OATV9	
	Tel: +1 800-638-0125, +1 860-827-0626	
	techsupport@microcare.com	
Emergency telephone number	-	
Emergency telephone	INFOTRAC 1-800-535-5053 (CANADA and U.S.A.)	
	1-352-323-3500 (from anywhere in the world)	
2. Hazard identification		
Classification of the substance	er mixture	
Physical hazards	Flam. Liq. 2 - H225	
Health hazards	Not Classified	
Environmental hazards	Aquatic Acute 1 - H400 Aquatic Chronic 2 - H411	
Human health	Splashes in the eyes may cause redness and irritation. Keep out of the reach of children. See Section 11 for additional information on health hazards.	
Physicochemical	The product is highly flammable. Vapours may form explosive mixtures with air.	
Label elements		
Hazard pictograms		
o	_	

Signal word

Danger

60-100%

10-30% Trade secret

DC1 - NO-CLEAN FLUX REMOVER, VERICLEAN - BULK

Hazard statements	H225 Highly flammable liquid and vapour. H400 Very toxic to aquatic life.
Precautionary statements	 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground and bond container and receiving equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P273 Avoid release to the environment. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
Supplemental label information	Safety data sheet available on request. For use in industrial installations only.

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

HEXAMETHYLDISILOXANE (Methyl siloxane)

CAS number: 107-46-0

M factor (acute) = 1

Classification

Flam. Liq. 2 - H225 Aquatic Acute 1 - H400 Aquatic Chronic 2 - H411

1-METHOXY-2-PROPANOL

CAS number: 107-98-2

Classification Flam. Liq. 3 - H226 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

Composition comments Not applicable.

Composition

4. First-aid measures		
Description of first aid measu	cription of first aid measures	
General information	Promptly remove any clothing that becomes wet or contaminated. Move affected person to fresh air at once. Get medical attention if any discomfort continues.	
Inhalation	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.	
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Never give anything by mouth to an unconscious person. Consult a physician for specific advice.	
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.	

Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.		
Most important symptoms and	Most important symptoms and effects, both acute and delayed		
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.		
Indication of any immediate me	edical attention and special treatment needed		
Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.		
5. Fire-fighting measures			
Extinguishing media			
Suitable extinguishing media	Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.		
Specific hazards arising from the	he hazardous product		
Specific hazards	The product is flammable. Heating may generate flammable vapours. Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3.		
Advice for firefighters			
Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.		
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.		
6. Accidental release measure	S		
Personal precautions, protectiv	e equipment and emergency procedures		
Personal precautions	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.		
Environmental precautions			
Environmental precautions	Do not discharge into drains or watercourses or onto the ground. Never use water by itself on spillage; this will spread the spill and cause further contamination.		
Methods and material for conta	ainment and cleaning up		
Methods for cleaning up	Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. If leakage cannot be stopped, evacuate area. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.		
7. Handling and storage			
Precautions for safe handling			
Usage precautions	Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Keep out of the reach of children.		
Conditions for safe storage, inc	cluding any incompatibilities		
Storage precautions	Keep away from heat, sparks and open flame.		
Specific end use(s)			

Specific end use(s) The identified uses for this product are detailed in Section 1.

Reference to other sections. Store away from incompatible materials (see Section 10).

8. Exposure controls/Personal protection

Control parameters

Occupational exposure li	mits
1-METHOXY-2-PROPAN	IOL

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm 184 mg/m³ Short-term exposure limit (15-minute): ACGIH 100 ppm 369 mg/m³ A4

ACGIH = American Conference of Governmental Industrial Hygienists. A4 = Not Classifiable as a Human Carcinogen.

Exposure controls

Protective equipment

Appropriate engineering controls	Provide adequate general and local exhaust ventilation.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene measures	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes wet or contaminated. When using do not eat, drink or smoke.
Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Clear liquid. Colourless.
Odour	Slight. Ether.
Odour threshold	No information available.
рН	No information available.
Melting point	No information available.
Initial boiling point and range	98°C/210°F @ 101.3 kPa
Flash point	-4.0°C/25°F Method: Tag closed cup.
Evaporation rate	No information available.

Evaporation factor	No information available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 18.6 %(V) Lower flammable/explosive limit: 1.25 %(V)
Vapour pressure	5.95 kPa @ 20°C
Vapour density	> 1.0
Relative density	No information available.
Bulk density	No information available.
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	365°C/689°F
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Global Warming Potential (GWP)	
Surface tension	
Refractive index	No information available.
Particle size	Not applicable.
Molecular weight	Not applicable.
Volatility	100%
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	This product contains a maximum VOC content of 87 g/litre.
Heat of vaporization (at boiling point), cal/g (Btu/lb)	
10. Stability and reactivity	
Reactivity	There are no known reactivity hazards associated with this product.
Stability	Stable at normal ambient temperatures.
Possibility of hazardous reactions	Will not polymerize.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidizing agents. Strong alkalis. Strong mineral acids.
Materials to avoid	Strong oxidizing agents.

Hazardous products	decomposition	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Vapours/gases/fumes of: Silicon dioxide Formaldehyde	
11. Toxicol	1. Toxicological information		
Information	on toxicological ef	<u>is</u>	
Other health effects There		here is no evidence that the product can cause cancer.	
Inhalation	halation May cause respiratory system irritation. Vapours may cause headache, fatigue, dizzinese nausea. Prolonged inhalation of high concentrations may damage respiratory system.		-
Ingestion		o harmful effects expected from quantities likely to be ingested	l by accident.
Skin contac	t	roduct has a defatting effect on skin. May cause skin irritation/	eczema.
Eye contac	t	ritating to eyes.	
Toxicologic	al information on ir	dients	
		HEXAMETHYLDISILOXANE (Methyl siloxane)	
	Acute toxicity - in	lation	
	Acute toxicity inh (LC₅₀ vapours mo	tion 106.0	
	Species	Rat	
12. Ecologi	cal information		
Ecotoxicity	xicity There are no data on the ecotoxicity of this product.		
Ecological i	Ecological information on ingredients		
		HEXAMETHYLDISILOXANE (Methyl siloxane)	
	Toxicity	Very toxic to aquatic organisms.	
	Acute aquatic to	<u>y</u>	
	LC50/EC50	$0.1 < L(E)C50 \le 1$	
	M factor (acute)	1	
	Acute toxicity - fis	LC₅₀, 96 hours: 0.46 mg/l mg/l, Fish	
	Acute toxicity - a invertebrates	tic EC₅₀, 72 hours: 0.79 mg/l, Daphnia magna	
	Acute toxicity - ad plants	tic EC₅₀, 96 hours: > 0.93 mg/l, Selenastrum capricornut	ım
Persistence	and degradability		
Persistence	and degradability	here are no data on the degradability of this product.	
Bioaccumu	lative potential		
Bioaccumu	lative potential	o data available on bioaccumulation.	
Partition co	efficient	o information available.	
Mobility in a	soil		
Mobility		he product contains volatile substances which may spread in t	he atmosphere.

Other adverse effects	
Other adverse effects	Not available.
13. Disposal considerations	
Waste treatment methods	
General information	Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
14. Transport information	
UN number	
UN No. (IMDG)	UN1993
UN No. (ICAO)	UN1993
UN proper shipping name	
Proper shipping name (TDG)	UN1993, FLAMMABLE LIQUID, N.O.S.(Hexamethyldisiloxane), 3, PGII
Proper shipping name (IMDG)	UN1993, FLAMMABLE LIQUID, N.O.S.(Hexamethyldisiloxane), 3, PGII
Proper shipping name (ICAO)	UN1993, FLAMMABLE LIQUID, N.O.S.(Hexamethyldisiloxane), 3, PGII
Proper shipping name (DOT)	UN1993, FLAMMABLE LIQUID, N.O.S.(Hexamethyldisiloxane), 3, PGII
Transport hazard class(es)	
TDG class	3
IMDG class	3
ICAO class/division	3
Packing group	
TDG packing group	II
IMDG packing group	II
ICAO packing group	II
DOT packing group	II
Environmental hazards	
Environmentally hazardous su	bstance/marine pollutant
Special precautions for user	
EmS	F-E, S-E
Transport in bulk according to	Not applicable

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

Inventories

Canada – DSL/NDSL Yes DSL

US - TSCA Yes

16. Other information	
Revision date	2021-06-01
Revision	39
Supersedes date	2020-03-13
SDS number	BULK - DC1
SDS status	Approved.
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.