



SAFETY DATA SHEET

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

1. Identification

Product identifier

Product name HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Product number MCC-SPRL, MCC-SPRG, MCC-SPRP, MCC-SPRD, MCC-SPRGL, MCC-SPRGG

Synonyms; Common Names "SPR - SUPRCLEAN Nonflammable Flux Remover"

Recommended use of the chemical and restrictions on use

Restriction on use Cleaning agent.

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier MICROCARE LLC

Manufacturer MICROCARE LLC
595 John Downey Drive
New Britain, CT 06051
United States of America
CAGE: OATV9
Tel: +1 800-638-0125, +1 860-827-0626
techsupport@microcare.com

Emergency telephone number

Emergency telephone INFOTRAC 1-800-535-5053 (CANADA and U.S.A.)
1-352-323-3500 (from anywhere in the world)

2. Hazard identification

Classification of the substance or mixture

WHMIS Regulatory Status This product has been classified according to the hazard criteria of the Hazardous Product Regulations and the SDS contains all required information.

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H332 Eye Irrit. 2A - H319 Repr. 1A - H360 STOT SE 3 - H336


Environmental hazards Aquatic Chronic 3 - H412

Physicochemical Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Gas or vapour displaces oxygen available for breathing (asphyxiant).

Label elements

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Hazard pictograms



Signal word	Danger
Hazard statements	H332 Harmful if inhaled. H319 Causes serious eye irritation. H360 May damage fertility or the unborn child. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P314 Get medical advice/ attention if you feel unwell. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	Safety data sheet available on request. For use in industrial installations only.
Contains	trans-1,2-DICHLOROETHYLENE, METHANOL

Other hazards

This product contains a substance classified as PBT.

3. Composition/information on ingredients

Mixtures

trans-1,2-DICHLOROETHYLENE CAS number: 156-60-5	60-80% Trade secret
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 Eye Irrit. 2A - H319 STOT SE 3 - H336 Aquatic Chronic 3 - H412	
1,1,1,2,2,3,4,5,5,5-decafluoropentane CAS number: 138495-42-8	15-40% Trade secret
Classification Aquatic Chronic 3 - H412	
Ethanol CAS number: 64-17-5	5-10%
Classification Flam. Liq. 2 - H225 Eye Irrit. 2A - H319	

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

METHANOL	0.1-1% Trade secret
CAS number: 67-56-1	
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
Eye Irrit. 2A - H319	
Repr. 1A - H360	
STOT SE 1 - H370	
ETHYL ACETATE	0.1-1% Trade secret
CAS number: 141-78-6	
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
ISOBUTYL METHYL KETONE	0.1-1% Trade secret
CAS number: 108-10-1	
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H332	
Eye Irrit. 2 - H319	
STOT SE 3 - H335	
HEXANE-norm	<1%
CAS number: 110-54-3	
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
Repr. 2 - H361f	
STOT SE 3 - H336	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

CYCLOHEXANE	<1%
CAS number: 110-82-7	
M factor (acute) = 1	M factor (chronic) = 1
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

Composition

4. First-aid measures

Description of first aid measures

General information	If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place. Get medical attention.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin contact	Rinse with water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Headache. Exhaustion and weakness.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	Irritating to eyes.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the hazardous product

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. This product is toxic.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

Advice for firefighters

Protective actions during firefighting Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Avoid breathing fire gases or vapours. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Avoid inhalation of vapours and spray/mists. Use suitable respiratory protection if ventilation is inadequate.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Provide adequate ventilation. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. For waste disposal, see Section 13.

Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.
<u>Conditions for safe storage, including any incompatibilities</u>	
Storage precautions	Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.
Storage class	Miscellaneous hazardous material storage.
<u>Specific end use(s)</u>	
Specific end use(s)	The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

trans-1,2-DICHLOROETHYLENE

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 793 mg/m³

Ethanol

Short-term exposure limit (15-minute): ACGIH 1000 ppm 1880 mg/m³

A3

METHANOL

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 262 mg/m³

Short-term exposure limit (15-minute): ACGIH 250 ppm 328 mg/m³

Sk

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): ACGIH 400 ppm 1440 mg/m³

ISOBUTYL METHYL KETONE

Long-term exposure limit (8-hour TWA): ACGIH 20 ppm 82 mg/m³

Short-term exposure limit (15-minute): ACGIH 75 ppm 307 mg/m³

A3

HEXANE-norm

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm 176 mg/m³

Sk

CYCLOHEXANE

Long-term exposure limit (8-hour TWA): ACGIH 100 ppm 344 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

Sk = Danger of cutaneous absorption.

Exposure controls

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

No specific hand protection recommended. Avoid contact with skin.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

Respiratory protection

Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Full face mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work.

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Colourless.
Odour	Slight. Ether.
Odour threshold	No information available.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	41°C/106°F @ 101.3 kPa
Flash point	The product is not flammable.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	Not applicable.

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 14.4 %(V) Lower flammable/explosive limit: 5.0 %(V)
Other flammability	The product is not flammable.
Vapour pressure	37.9 kPa @ 20°C
Vapour density	3.4
Relative density	1.26 g/cc
Bulk density	No information available.
Solubility(ies)	0.3 % water @ 20°C
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	0.48 cP @ 20°C
Explosive properties	No information available.
Oxidising properties	Not known.
Global Warming Potential (GWP)	
Surface tension	
Refractive index	No information available.
Particle size	No information available.
Molecular weight	Not applicable.
Volatility	100%
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	This product contains a maximum VOC content of 1080 g/l.
Heat of vaporization (at boiling point), cal/g (Btu/lb)	

10. Stability and reactivity

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 7,936.51

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 119,047.62

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Acute Tox. 4 - H332 Harmful if inhaled.

ATE inhalation (vapours mg/l) 15.91

ATE inhalation (dusts/mists mg/l) 198.41

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance/a group of substances which may cause cancer. IARC Group 1
Carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Headache. Exhaustion and weakness.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	No specific symptoms known.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target organs	No specific target organs known.

Toxicological information on ingredients

trans-1,2-DICHLOROETHYLENE

Other health effects	There is no evidence that the product can cause cancer.
<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	7,902.0
Species	Rat
ATE oral (mg/kg)	7,902.0
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	5,000.0
Species	Rat
ATE dermal (mg/kg)	5,000.0
<u>Acute toxicity - inhalation</u>	
ATE inhalation (vapours mg/l)	11.0
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Prolonged and frequent contact may cause redness and irritation.
Animal data	Slightly irritating. Rabbit
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Supplier's information. Rabbit 500 mg 24 hours Causes mild skin irritation.
<u>Respiratory sensitization</u>	
Respiratory sensitization	No specific test data are available.
<u>Skin sensitization</u>	
Skin sensitization	No specific test data are available.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	This substance has no evidence of mutagenic properties.
Genotoxicity - in vivo	This substance has no evidence of mutagenic properties.

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Carcinogenicity

Carcinogenicity No specific test data are available.

Specific target organ toxicity - single exposure

STOT - single exposure NOAEL Not available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 16 mg/l, 90 days

Target organs Endocrine system Liver Kidneys Bladder Respiratory tract

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE dermal (mg/kg) 5,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 114.0

Species Rat

ATE inhalation (vapours mg/l) 114.0

Skin corrosion/irritation

Animal data Not irritating. Rabbit

Human skin model test Data lacking.

Extreme pH Not applicable. Not corrosive to skin.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating. Rabbit

Respiratory sensitization

Respiratory sensitization Data lacking.

Skin sensitization

Skin sensitization Not sensitising. - Guinea pig: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro This substance has no evidence of mutagenic properties.

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Genotoxicity - in vivo	This substance has no evidence of mutagenic properties.
<u>Carcinogenicity</u>	
Carcinogenicity	Does not contain any substances known to be carcinogenic.
IARC carcinogenicity	Not listed.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No evidence of reproductive toxicity in animal studies.
<u>Skin contact</u>	
Skin contact	Skin irritation should not occur when used as recommended. May cause defatting of the skin but is not an irritant.
<u>Eye contact</u>	
Eye contact	May cause eye irritation.
<u>Acute and chronic health hazards</u>	
Acute and chronic health hazards	There is no evidence that the product can cause cancer.

METHANOL

Acute toxicity - oral

Notes (oral LD₅₀) Acute Tox. 3 - H301 Toxic if swallowed.

ATE oral (mg/kg) 100.0

Acute toxicity - dermal

Notes (dermal LD₅₀) Acute Tox. 3 - H311 Toxic in contact with skin.

ATE dermal (mg/kg) 300.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Acute Tox. 3 - H331 Toxic if inhaled.

ATE inhalation (vapours mg/l) 3.0

ATE inhalation (dusts/mists mg/l) 0.5

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	None of the ingredients are listed or exempt.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	STOT SE 1 - H370 Causes damage to organs .
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo. Unconsciousness. High concentrations may be fatal.
Ingestion	May cause stomach pain or vomiting. May cause severe internal injury.
Skin contact	A single exposure may cause the following adverse effects: Pain.
Eye contact	No specific symptoms known.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target organs	No specific target organs known.

ISOBUTYL METHYL KETONE

<u>Carcinogenicity</u>	
IARC carcinogenicity	IARC Group 2B Possibly carcinogenic to humans.

12. Ecological information

Ecological information on ingredients

trans-1,2-DICHLOROETHYLENE

Ecotoxicity	Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.
--------------------	--

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Ecotoxicity	It is unlikely that the substance will dissolve in water in amounts big enough to have a toxic effect on fish and daphnies.
--------------------	---

METHANOL

Ecotoxicity	Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.
--------------------	---

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Toxicity Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

Ecological information on ingredients

trans-1,2-DICHLOROETHYLENE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 135 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 220 mg/l, Daphnia magna

Acute toxicity - aquatic plants LC₅₀, 72 hours: 36.36 mg/l, Pseudokirchneriella subcapitata

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOEC, 48 hours: 110,000 mg/l, Daphnia magna

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 13.9 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates LC₅₀, 48 hours: 11.7 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: >120 mg/l, Algae

METHANOL

Toxicity Based on available data the classification criteria are not met.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >100 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >10000 mg/l, Daphnia magna

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients

trans-1,2-DICHLOROETHYLENE

Biodegradation Not readily biodegradable.
Method: OECD Test Guideline 301D

METHANOL

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Ecological information on ingredients

trans-1,2-DICHLOROETHYLENE

Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.
Partition coefficient	log Pow: 2.06

1,1,1,2,2,3,4,5,5,5-decafluoropentane

Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.
Partition coefficient	Pow: 2.7

METHANOL

Bioaccumulative potential	No data available on bioaccumulation.
Partition coefficient	: -0.77

Mobility in soil

Mobility	No data available.
-----------------	--------------------

Ecological information on ingredients

trans-1,2-DICHLOROETHYLENE

Mobility	The product has poor water-solubility.
-----------------	--

METHANOL

Mobility	No data available.
-----------------	--------------------

Other adverse effects

Other adverse effects	None known.
------------------------------	-------------

Ecological information on ingredients

METHANOL

Other adverse effects	None known.
------------------------------	-------------

13. Disposal considerations

Waste treatment methods

General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

14. Transport information

General Not regulated. The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, TDG).

UN number

UN proper shipping name

Proper shipping name (TDG) Not Hazardous Not Regulated

Proper shipping name (IMDG) Not Hazardous Not Regulated

Proper shipping name (ICAO) Not Hazardous Not Regulated

Proper shipping name (DOT) Not Hazardous Not Regulated

Transport hazard class(es)

Transport Labels (International) Not applicable., No information required.

Packing group

Packing group (International) No information required.

Special precautions for user

Not applicable. No information required.

15. Regulatory information

Inventories

Canada – DSL/NDSL

All the ingredients are listed or exempt.

DSL

trans-1,2-DICHLOROETHYLENE

DSL

1,1,1,2,2,3,4,5,5,5-decafluoropentane

DSL

16. Other information

Classification abbreviations and acronyms Acute Tox. = Acute toxicity
Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Training advice Only trained personnel should use this material.

Revision date 2021-05-25

Revision 47

Supersedes date 2021-05-25

SDS number BULK - SPR

HEAVY DUTY FLUX REMOVER - SUPRCLEAN, BULK

Hazard statements in full

H225 Highly flammable liquid and vapour.
H301 Toxic if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360 May damage fertility or the unborn child.
H361f Suspected of damaging fertility.
H370 Causes damage to organs .
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.