

SAFETY DATA SHEET IPA Based Presaturated Wipes IsoClean™

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

1. Identification	
Product identifier	
Product name	IPA Based Presaturated Wipes IsoClean™
Product number	MCC-BACW, MCC-BACWR
Recommended use of the che	emical and restrictions on use
Restriction on use	Cleaning agent.
Uses advised against	No specific uses advised against are identified.
Details of the supplier of the s	afety data sheet
Supplier	MICROCARE LLC
Manufacturer	MICROCARE LLC 595 John Downey Drive New Britain, CT 06051 United States of America CAGE: OATV9 Tel: +1 800-638-0125, +1 860-827-0626 techsupport@microcare.com
Emergency telephone numbe	<u>r</u>
Emergency telephone	INFOTRAC 1-800-535-5053 (CANADA and U.S.A.) 1-352-323-3500 (from anywhere in the world)
2. Hazard identification	
Classification of the substance	e or mixture
Physical hazards	Flam. Liq. 2 - H225
Health hazards	Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards	Not Classified
Label elements	
Hazard pictograms	
Signal word	Danger
Hazard statements	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary statements	 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P312 Call a POISON CENTRE/doctor if you feel unwell. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH210 Safety data sheet available on request. RCH001b For use in industrial installations or professional treatment only.
Contains	PROPAN-2-OL

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

PROPAN-2-OL	60-100%
CAS number: 67-63-0	
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	

The full text for all hazard statements is displayed in Section 16.

Composition comments	TSCA: The ingredients of this product are on the TSCA Inventory. The exact percentage
	(concentration) of composition has been withheld as a trade secret in accordance with
	paragraph (i) of CFR 1900.1200

Composition

4. First-aid measures		
Description of first aid measures		
General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.	
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place.	
Ingestion	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical attention if symptoms are severe or persist.	
Skin contact	Rinse with water.	
Eye contact	Rinse with water. Do not rub eye. Remove any contact lenses and open eyelids wide apart. Get medical attention if any discomfort continues.	
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.	

Most important symptoms and effects, both acute and delayed

Narcotic effect. Muscle weakness. Nausea, vomiting. ngestion A single exposure may cause the following adverse effects: Intoxication. Nausea, vomiting. May cause drowsiness or dizziness. Central nervous system depression. May cause severe intermal injury. Skin contact A single exposure may cause the following adverse effects: Pain. Eye contact Irritating to eyes. ndication of any immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. 5. Fire-fighting measures	General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
May cause drowsiness or dizziness. Central nervous system depression. May cause severe internal injury. Skin contact A single exposure may cause the following adverse effects: Pain. Eye contact Irritating to eyes. Indication of any immediate medical attention and special treatment needed Votes for the doctor Treat symptomatically. 5. Fire-fighting measures Extinguishing media Sultable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Jusuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in severs may create fire or explosion hazard. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Advice for firefighters Protective actions during fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, furnes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray on dirence vapours and voriet them stopping the leak. Control run-off water by containing and keeping it out of severs and watercourses. If risk of water pollution occurs,	Inhalation	
Eye contact Irritating to eyes. indication of any immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. 5. Fire-fightling measures Extinguishing media Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Jnsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Specific hazards arising from the hazardous product Specific hazards Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Hazardous combustion Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Advice for firefighters Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to fate with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authoritites. Spe	Ingestion	May cause drowsiness or dizziness. Central nervous system depression. May cause severe
Indication of any immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. 5. Fire-fighting measures	Skin contact	A single exposure may cause the following adverse effects: Pain.
Notes for the doctor Treat symptomatically. 5. Fire-fighting measures Extinguishing media Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Jnsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Specific hazards arising from the hazardous product Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Hazardous combustion Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Advice for firefighters Protective actions during gase, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of severs and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment or firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective cothing. Firefighter'	Eye contact	Irritating to eyes.
5. Fire-fighting measures Extinguishing media Sultable extinguishing media Sultable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Do not use water jet as an extinguisher, as this will spread the fire. Specific hazards arising from the hazardous product Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Hazardous combustion Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Advice for firefighters Protective actions during irefighting Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disprese vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment or finefighters Harmful gase on occupational health and safety or by NFPA standards if applicable.	Indication of any immediate m	edical attention and special treatment needed
Extinguishing media Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Jnsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Specific hazards arising from the hazardous product Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Advice for firefighters Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment or firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational hea	Notes for the doctor	Treat symptomatically.
Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Jnsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Specific hazards arising from the hazardous product Specific hazards Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Advice for firefighters Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect me stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Ca	5. Fire-fighting measures	
or water fog. Use fire-extinguishing media suitable for the surrounding fire. Do not use water jet as an extinguisher, as this will spread the fire. Do not use water jet as an extinguisher, as this will spread the fire. Specific hazards arising from the hazardous product Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Hazardous combustion Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Advice for firefighters Protective actions during irefighting Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment or firefighters Over the pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Extinguishing media	
nedia Specific hazards arising from the hazardous product Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Advice for firefighters Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment or firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Suitable extinguishing media	
Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Advice for firefighters Protective actions during irefighting Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.Hazardous combustion productsThermal decomposition or combustion products may include the following substances: Harmful gases or vapours.Advice for firefightersProtective actions during gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect ments of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Specific hazards arising from t	he hazardous product
broductsHarmful gases or vapours.Advice for firefightersProtective actions during irefightingAvoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Specific hazards	Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or
Protective actions during irrefightingAvoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Hazardous combustion products	
irefightinggases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping 	Advice for firefighters	
or firefighters clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.	Protective actions during firefighting	gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If
3. Accidental release measures	Special protective equipment for firefighters	clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial
	6. Accidental release measure	S

Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of vapours and spray/mists. Use suitable respiratory protection if ventilation is inadequate.
Environmental precautions Environmental precautions	Avoid discharge into drains or watercourses or onto the ground.
Methods and material for conta	ainment and cleaning up
Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. The contaminated absorbent may pose the same hazard as the spilled material. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.
Reference to other sections	
Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
7. Handling and storage	
Precautions for safe handling	
Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.
Conditions for safe storage, including any incompatibilities	
Storage precautions	Store away from incompatible materials (see Section 10). Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.
Storage class	Flammable liquid storage.
Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.
Reference to other sections.	Store away from incompatible materials (see Section 10).
8. Exposure controls/Personal protection	

Control parameters

Occupational exposure limits

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³ Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³ A4

ACGIH = American Conference of Governmental Industrial Hygienists. A4 = Not Classifiable as a Human Carcinogen.

Exposure controls

Protective equipment



Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full- face respirator may be required instead.
Hand protection	No specific hand protection recommended.
Other skin and body protection	Wear appropriate clothing to prevent repeated or prolonged skin contact.
Hygiene measures	Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.
Respiratory protection	Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Full face mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation regulation on health and safety at work. SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work. SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work. SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Information on basic physical and chemical properties	
Appearance	Clear liquid.
Colour	Colourless.
Odour	Alcoholic.
Odour threshold	No information available.
рН	No information available.

Melting point	No information available.
Initial boiling point and range	82°C/180°F @ 101.3 kPa
Flash point	12°C/53°F Tag closed cup.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 2.0 %(V) Upper flammable/explosive limit: 12.7 %(V)
Other flammability	No information available.
Vapour pressure	5.2 kPa @ 20°C
Vapour density	1.82
Relative density	No information available.
Bulk density	No information available.
Solubility(ies)	Soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Oxidising properties	There are no chemical groups present in the product that are associated with oxidizing properties.
Comments	Information given is applicable to the major ingredient.
Global Warming Potential (GWP)	
Surface tension	
Refractive index	No information available.
Particle size	Not applicable.
Molecular weight	No information available.
Volatility	100%
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	This product contains a maximum VOC content of 100 %.
Heat of vaporization (at boiling point), cal/g (Btu/lb)	
10. Stability and reactivity	

Reactivity

See the other subsections of this section for further details.

Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	The following materials may react strongly with the product: Oxidizing agents.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.
Materials to avoid	Oxidizing materials. Acids - oxidizing.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.
11. Toxicological information	
Information on toxicological ef	fects
<u>Acute toxicity</u> - oral Notes (oral LD∞)	Based on available data the classification criteria are not met.
Acute toxicity - dermal Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
Acute toxicity - inhalation Notes (inhalation LC ₅₀)	Based on available data the classification criteria are not met.
Skin corrosion/irritation Animal data	Based on available data the classification criteria are not met.
Serious eye damage/irritation Serious eye damage/irritation	Causes serious eye irritation.
Respiratory sensitization Respiratory sensitization	Based on available data the classification criteria are not met.
Skin sensitization Skin sensitization	Based on available data the classification criteria are not met.
Germ cell mutagenicity Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Carcinogenicity Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	Contains a substance/a group of substances which may cause cancer. IARC Group 1 Carcinogenic to humans.
Reproductive toxicity	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
Specific target organ toxicity -	single exposure
STOT - single exposure	STOT SE 3 - H336 May cause drowsiness or dizziness. STOT SE 2 - H371 May cause damage to organs .

Target organ	S	Central nervous system	
Specific target organ toxicity - repeated exposure			
	ated exposure		
Aspiration ha	azard		
Aspiration ha	azard	Based on available data the classification criteria are not met.	
General infor	mation	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.	
Inhalation		A single exposure may cause the following adverse effects: Pain or irritation. Intoxication. Narcotic effect. Muscle weakness. Nausea, vomiting.	
Ingestion		A single exposure may cause the following adverse effects: Intoxication. Nausea, vomiting. May cause drowsiness or dizziness. Central nervous system depression. May cause severe internal injury.	
Skin contact		A single exposure may cause the following adverse effects: Pain.	
Eye contact		Irritating to eyes.	
Acute and ch hazards	nronic health	Keep out of the reach of children.	
Route of exp	osure	Ingestion Inhalation Skin and/or eye contact	
Target organ	s	Central nervous system	
Toxicological	l information on in	ngredients	
		PROPAN-2-OL	
	Carcinogenicity		
	IARC carcinogen	icity IARC Group 3 Not classifiable as to its carcinogenicity to humans.	
	NTP carcinogenicity Not listed.		
12. Ecologica	al information		
Ecotoxicity		There are no data on the ecotoxicity of this product.	
Toxicity	oxicity Not considered toxic to fish.		
Ecological in	formation on ingre	edients	
PROPAN-2-OL			
	Acute aquatic to	kicity	
	Acute toxicity - fis	sh LC₅₀, 96 hours: 9,640 mg/l, Fish	
	Acute toxicity - ad invertebrates	quatic EC₅₀, 48 hours: 5102 mg/l, Daphnia magna	
	Acute toxicity - ad plants	quatic IC₅₀, 72 hours: >2,000 mg/l, Algae	
Persistence :	and degradability		

Persistence and degradability

Persistence and degradability The product contains only inorganic substances which are not biodegradable.

Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
Partition coefficient	No information available.
Ecological information on ingredients	
	PROPAN-2-OL
Partition coefficie	nt : 0.05
Mobility in soil	
Mobility	No data available.
Other adverse effects	
Other adverse effects	None known.
13. Disposal considerations	
Waste treatment methods	
General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.
14. Transport information	
The transport internation	
General	Requirements for marking and labeling of package varies depending on mode of transport. If uncertain of proper markings and labeling, call MicroCare for assistance.
General	uncertain of proper markings and labeling, call MicroCare for assistance.
General Air transport notes	uncertain of proper markings and labeling, call MicroCare for assistance. Forbidden for passenger and cargo aircraft.
General Air transport notes DOT transport notes	uncertain of proper markings and labeling, call MicroCare for assistance. Forbidden for passenger and cargo aircraft.
General Air transport notes DOT transport notes <u>UN number</u>	uncertain of proper markings and labeling, call MicroCare for assistance. Forbidden for passenger and cargo aircraft. As supplied, this product is consigned under the Limited Quantities provisions.
General Air transport notes DOT transport notes <u>UN number</u> UN No. (IMDG)	uncertain of proper markings and labeling, call MicroCare for assistance. Forbidden for passenger and cargo aircraft. As supplied, this product is consigned under the Limited Quantities provisions.
General Air transport notes DOT transport notes <u>UN number</u> UN No. (IMDG) <u>UN proper shipping name</u>	uncertain of proper markings and labeling, call MicroCare for assistance. Forbidden for passenger and cargo aircraft. As supplied, this product is consigned under the Limited Quantities provisions. 3175 LIMITED QUANTITY
General Air transport notes DOT transport notes <u>UN number</u> UN No. (IMDG) <u>UN proper shipping name</u> Proper shipping name (TDG)	 uncertain of proper markings and labeling, call MicroCare for assistance. Forbidden for passenger and cargo aircraft. As supplied, this product is consigned under the Limited Quantities provisions. 3175 LIMITED QUANTITY UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.(Isopropanol), 4.1, PGII,
General Air transport notes DOT transport notes <u>UN number</u> UN No. (IMDG) <u>UN proper shipping name</u> Proper shipping name (TDG) Proper shipping name (IMDG)	uncertain of proper markings and labeling, call MicroCare for assistance. Forbidden for passenger and cargo aircraft. As supplied, this product is consigned under the Limited Quantities provisions. 3175 LIMITED QUANTITY UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.(Isopropanol), 4.1, PGII, LIMITED QUANTITY
General Air transport notes DOT transport notes <u>UN number</u> UN No. (IMDG) <u>UN proper shipping name</u> Proper shipping name (TDG) Proper shipping name (IMDG)	uncertain of proper markings and labeling, call MicroCare for assistance. Forbidden for passenger and cargo aircraft. As supplied, this product is consigned under the Limited Quantities provisions. 3175 LIMITED QUANTITY UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.(Isopropanol), 4.1, PGII, LIMITED QUANTITY Forbidden for passenger and cargo aircraft.
General Air transport notes DOT transport notes <u>UN number</u> UN No. (IMDG) <u>UN proper shipping name</u> Proper shipping name (TDG) Proper shipping name (IMDG) Proper shipping name (ICAO) Proper shipping name (DOT)	uncertain of proper markings and labeling, call MicroCare for assistance. Forbidden for passenger and cargo aircraft. As supplied, this product is consigned under the Limited Quantities provisions. 3175 LIMITED QUANTITY UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.(Isopropanol), 4.1, PGII, LIMITED QUANTITY Forbidden for passenger and cargo aircraft.
General Air transport notes DOT transport notes <u>UN number</u> UN No. (IMDG) <u>UN proper shipping name</u> Proper shipping name (TDG) Proper shipping name (IMDG) Proper shipping name (ICAO) Proper shipping name (DOT) <u>Transport hazard class(es)</u>	uncertain of proper markings and labeling, call MicroCare for assistance. Forbidden for passenger and cargo aircraft. As supplied, this product is consigned under the Limited Quantities provisions. 3175 LIMITED QUANTITY UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.(Isopropanol), 4.1, PGII, LIMITED QUANTITY Forbidden for passenger and cargo aircraft. LIMITED QUANTITY

IPA Based Presaturated Wipes IsoClean™

ibstance/marine pollutant
F-A, S-I
No information required. Not applicable.
Flam. Liq. = Flammable liquid Eye Irrit. = Eye irritation STOT SE = Specific target organ toxicity-single exposure
Only trained personnel should use this material.
NOTE: Lines within the margin indicate significant changes from the previous revision.
2021-06-01
35
2020-10-09
PRESAT - BACW
Approved.
H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.