

SAFETY DATA SHEET ALCOHOL-ENHANCED PRESATURATED WIPES, PROCLEAN

According to the Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013, as amended.

SECTION 1: identification of the hazardous chemical and of the supplier

Product identifier

Product name ALCOHOL-ENHANCED PRESATURATED WIPES, PROCLEAN

Product number MCC-PROW, MCC-PROWR, MCC-PROWY, MCC-PROWYR

Synonyms; trade names "PROW-ProClean Solvent Presaturated Wipes"; "PROWR-Stencil Wipes with ProClean

Presaturated Wipes/Refill"

Recommended use of the substance or mixture and restrictions on use

Identified uses Cleaning agent.

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier MICROCARE ASIA PTE LTD

102E, Pasir Panjang Road,

Citilink, #05-06, Singapore 118529 Phone (65)6271.0182 techsupport@microcare.sg

Manufacturer MICROCARE LLC

595 John Downey Drive New Britain, CT 06051 United States of America

CAGE: OATV9

Tel: +1 800-638-0125, +1 860-827-0626

techsupport@microcare.com

Emergency telephone number

Emergency telephone INFOTRAC +65 3163 5349 (SINGAPORE)

1-352-323-3500 (from anywhere in the world)

SECTION 2: Hazard identification

Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Not Classified

Label elements

Pictogram





Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements P210 Keep away from heat/ sparks/ open flames /hot surfaces – No smoking.

P261 Avoid breathing vapour/ spray.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/ attention if you feel unwell.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

Supplemental label

information

Safety data sheet available on request. For use in industrial installations only.

Contains PROPAN-2-OL

Supplementary precautionary

statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P240 Ground/ bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe vapour/ spray.

P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink, or smoke when using this product.

P271 Use only outdoors or in a wellventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/ take off immediately all contaminated

clothing. Rinse skin with water/ shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor/ physician.

P308+P313 IF exposed or concerned: Get medical advice/attention. P312 Call a POISON CENTER or doctor/ physician if you feel unwell.

P321 Specific treatment (see medical advice on this label).

P337+P313 If eye irritation persists: Get medical advice/ attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

Other hazards

This product contains a substance classified as PBT (persistent, bioaccumulative and toxic).

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Mixtures

ALCOHOL-ENHANCED PRESATURATED WIPES, PROCLEAN

Denatured Ethanol B100 30-60%

CAS number: 64-17-5

Classification Flam. Liq. 2 - H225

PROPAN-2-OL 30-60%

CAS number: 67-63-0

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage (concentration) of composition has been withheld as a trade secret in

accordance with paragraph (i) of CFR 1900.1200 TSCA: The ingredients of this product are

on the TSCA Inventory.

Composition

SECTION 4: First-aid measures

Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical

personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery

position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if

the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical

attention if symptoms are severe or persist.

Skin contact Rinse with water.

Eye contact Rinse with water. Do not rub eye. Remove any contact lenses and open eyelids wide apart.

Get medical attention if any discomfort continues.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation A single exposure may cause the following adverse effects: Pain or irritation. Intoxication.

Narcotic effect. Muscle weakness. Nausea, vomiting.

Ingestion A single exposure may cause the following adverse effects: Intoxication. Nausea, vomiting.

May cause drowsiness or dizziness. Central nervous system depression. May cause severe

internal injury.

ALCOHOL-ENHANCED PRESATURATED WIPES, PROCLEAN

Skin contact A single exposure may cause the following adverse effects: Pain.

Eye contact Irritating to eyes.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder

or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

> Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or

explosion hazard.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapours.

Advice for fire-fighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Fire-fighter's clothing will provide a basic level of protection for chemical incidents.

Hazchem code 1Z

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be Personal precautions

> taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes

> contaminated. Avoid inhalation of vapours and spray/mists. Use suitable respiratory protection

if ventilation is inadequate.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. The contaminated absorbent may pose the same hazard as the spilled material. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store away from incompatible materials (see Section 10). Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

Storage class

Flammable liquid storage.

Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.

SECTION 8: Exposure controls and personal protection

Control parameters

Occupational exposure limits

Denatured Ethanol B100

Eight-hour time-weighted average: PEL 1000 ppm 1880 mg/m³

PROPAN-2-OL

Eight-hour time-weighted average: PEL 400 ppm 983 mg/m³

Permissible exposure limit (PEL)

Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the

product or ingredients.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-

face respirator may be required instead.

Hand protection No specific hand protection recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke

when using this product.

Respiratory protection Ensure all respiratory protective equipment is suitable for its intended use. Check that the

respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges suitable for intended use should be used. Full face mask respirators with replaceable filter cartridges suitable for intended use should be used. Half mask and quarter mask respirators

with replaceable filter cartridges suitable for intended use should be used.

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Colourless.

Odour threshold No information available.

PH No information available.

Alcoholic.

Melting point No information available.

Initial boiling point and range 77.6°C/172°F @ 101.3 kPa

Flash point 12°C/54°F Tag closed cup.

Evaporation rate No information available.

Evaporation factor No information available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Odour

Lower flammable/explosive limit: 2.0 Upper flammable/explosive limit: 12.7

Other flammability No information available.

Vapour pressure 5.2 kPa @ 20°C

ALCOHOL-ENHANCED PRESATURATED WIPES, PROCLEAN

Vapour density 1.82
Relative density 0.79

Bulk density Not applicable.

Soluble in water.

Partition coefficientNo information available.Auto-ignition temperatureNo information available.Decomposition temperatureNo information available.

Viscosity No information available.

Explosive properties The product is highly flammable. Vapours may form explosive mixtures with air.

Oxidising properties There are no chemical groups present in the product that are associated with oxidising

properties.

Comments Information given is applicable to the major ingredient.

Global Warming Potential

(GWP)

Surface tension

Refractive index

No information available.

Particle size

No information available.

Molecular weight

No information available.

Volatility 100%

Saturation concentration No information available.

Critical temperature No information available.

Volatile organic compound This product contains a maximum VOC content of 785 g/l.

Heat of vaporization (at boiling

point), cal/g (Btu/lb)

SECTION 10: Stability and reactivity

Reactivity See the other subsections of this section for further details.

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

The following materials may react strongly with the product: Oxidising agents.

Conditions to avoid Avoid heat, flames and other sources of ignition. Containers can burst violently or explode

when heated, due to excessive pressure build-up. Static electricity and formation of sparks

must be prevented.

Materials to avoid Oxidising materials. Acids - oxidising.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC50) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance/a group of substances which may cause cancer. IARC Group 1

Carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness. STOT SE 2 - H371 May cause

damage to organs.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure
Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazardBased on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation A single exposure may cause the following adverse effects: Pain or irritation. Intoxication.

Narcotic effect. Muscle weakness. Nausea, vomiting.

ALCOHOL-ENHANCED PRESATURATED WIPES, PROCLEAN

Ingestion A single exposure may cause the following adverse effects: Intoxication. Nausea, vomiting.

May cause drowsiness or dizziness. Central nervous system depression. May cause severe

internal injury.

Skin contact A single exposure may cause the following adverse effects: Pain.

Eye contact Irritating to eyes.

Acute and chronic health

hazards

Keep out of the reach of children.

Route of entry Ingestion Inhalation Skin and/or eye contact

Target organs Central nervous system

Toxicological information on ingredients

PROPAN-2-OL

Carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

Toxicity Based on available data the classification criteria are not met.

Ecological information on ingredients

PROPAN-2-OL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 9,640 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 5102 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

IC₅₀, 72 hours: >2,000 mg/l, Algae

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients

PROPAN-2-OL

Partition coefficient : 0.05

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal information

Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product

residues and hence be potentially hazardous.

Disposal methodsDo not empty into drains. Dispose of surplus products and those that cannot be recycled via a

licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is

not feasible.

SECTION 14: Transportation information

General Requirements for marking and labeling of package varies depending on mode of transport. If

uncertain of proper markings and labeling, call MicroCare for assistance.

Air transport notes Forbidden for passenger and cargo aircraft.

UN number

UN No. (IMDG) UN3175

UN proper shipping name

Proper shipping name

(Road/Rail) PGII, Limited Quantity

Proper shipping name

(IMDG)

UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Isopropanol Solution), 4.1,

UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Isopropanol Solution), 4.1,

PGII, Limited Quantity

Proper shipping name (ICAO) Forbidden for passenger and cargo aircrafts.

Transport hazard class(es)

Road/Rail class 4.1

Road/Rail classification code F1

Road/Rail label 4.1

IMDG class 4.1

Packing group

Road/Rail packing group

IMDG packing group

Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

Special precautions for user

EmS F-A, S-I

Hazard Identification Number 40 (Road/Rail)

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the substance or mixture

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

IATA: International air transport association.

ICAO: Technical instructions for the safe transport of dangerous goods by air.

IMDG: International maritime dangerous goods.

CAS: Chemical abstracts service. ATE: Acute toxicity estimate.

LC₅₀: Lethal concentration to 50 % of a test population.

LD₅₀: Lethal dose to 50% of a test population (median lethal dose).

EC₅₀: 50% of maximal effective concentration.

PBT: Persistent, bioaccumulative and toxic substance. vPvB: Very persistent and very bioaccumulative.

Classification abbreviations

and acronyms

Flam. Liq. = Flammable liquid Eye Irrit. = Eye irritation

STOT SE = Specific target organ toxicity-single exposure

Training advice Only trained personnel should use this material.

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 21/5/2021

Revision 36

Supersedes date 12/3/2021

SDS number PRESAT - PRO

SDS status Approved.

Hazard statements in full H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.