

SAFETY DATA SHEET CDI - STENCIL, SQUEEGEE and MISPRINT CLEANER, BULK

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

1. Identification

Product identifier

Product name CDI - STENCIL, SQUEEGEE and MISPRINT CLEANER, BULK

Product number MCC-CDIG, MCC-CDIP, MCC-CDIG, MCC-CDIGL, MCC-CDIL

Recommended use of the chemical and restrictions on use

Uses advised againstNo specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier MICROCARE LLC

Manufacturer MICROCARE LLC

595 John Downey Drive New Britain, CT 06051 United States of America

CAGE: OATV9

Tel: +1 800-638-0125, +1 860-827-0626

techsupport@microcare.com

Emergency telephone number

Emergency telephone INFOTRAC 1-800-535-5053 (CANADA and U.S.A.)

1-352-323-3500 (from anywhere in the world)

2. Hazard identification

Classification of the substance or mixture

WHMIS Regulatory Status This product has been classified according to the hazard criteria of the Hazardous Product

Regulations and the SDS contains all required information.

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2A - H319

Environmental hazards Not Classified

Label elements

Hazard pictograms





Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/ attention.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label

information

Safety data sheet available on request. For use in industrial installations only.

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

1-propoxypropan-2-ol

60-80% Trade secret

CAS number: 1569-01-3

Classification

Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Irrit. 2A - H319

D.I. WATER

30-60% Trade secret

CAS number: 7732-18-5

Classification

Not Classified

ETHYL ACETATE

1-5% Trade secret

CAS number: 141-78-6

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

CDI - STENCIL, SQUEEGEE and MISPRINT CLEANER, BULK

PROPAN-2-OL 1-5% Trade secret

CAS number: 67-63-0

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

Composition comments Not applicable.

Composition

4. First-aid measures

Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical

personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms

are severe or persist.

Ingestion Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not

induce vomiting unless under the direction of medical personnel.

Skin contact Rinse with water.

Eye contact Rinse with water. Do not rub eye. Remove any contact lenses and open eyelids wide apart.

Get medical attention if any discomfort continues.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation No specific symptoms known.

Ingestion May cause irritation.

Skin contact Redness. Irritating to skin.

Eye contact Irritating to eyes.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder

or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the hazardous product

CDI - STENCIL, SQUEEGEE and MISPRINT CLEANER, BULK

Specific hazards

Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.

Hazardous combustion products

Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

Environmental precautions

Environmental precautions

Avoid discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. The contaminated absorbent may pose the same hazard as the spilled material. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash

contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Keep away from oxidizing materials,

heat and flames. Keep only in the original container. Keep container tightly closed, in a cool,

well ventilated place. Keep containers upright. Protect containers from damage.

Storage class Flammable liquid storage.

Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

Reference to other sections. Store away from incompatible materials (see Section 10).

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): ACGIH 400 ppm 1440 mg/m³

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³ Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³ A4

ACGIH = American Conference of Governmental Industrial Hygienists. A4 = Not Classifiable as a Human Carcinogen.

Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and any relevant provincial regulation relating to health and safety at work. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

CDI - STENCIL, SQUEEGEE and MISPRINT CLEANER, BULK

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke

when using this product.

Respiratory protection Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH

approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Full face mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial

regulation relating to health and safety at work.

Environmental exposure

controls

Keep container tightly sealed when not in use.

9. Physical and chemical properties

Information on basic physical and chemical properties

Melting point Not applicable.

Initial boiling point and range 120°C/249°F @ 101.3 kPa

Flash point 44°C/120°F Tag closed cup.

Evaporation rate

No information available.

Evaporation factor

No information available.

Upper/lower flammability or

explosive limits

Upper flammable/explosive limit: N/D Lower flammable/explosive limit: N/D

Vapour pressure 0.23 kPa @ 25°C

Vapour density 4.0

Relative density 0.97

Bulk density Not applicable.

Partition coefficient No information available.

Auto-ignition temperature No information available.

Decomposition Temperature No information available.

Viscosity Not applicable.

Global Warming Potential

(GWP)

Surface tension

Refractive index Not applicable.

Particle size Not applicable.

Molecular weight Not applicable.

Saturation concentration No information available.

CDI - STENCIL, SQUEEGEE and MISPRINT CLEANER, BULK

Critical temperature Not applicable.

Volatile organic compound This product contains a maximum VOC content of 785 g/l.

Heat of vaporization (at boiling

point), cal/g (Btu/lb)

10. Stability and reactivity

Reactivity See the other subsections of this section for further details.

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

The following materials may react strongly with the product: Oxidizing agents.

Conditions to avoid Avoid heat, flames and other sources of ignition. Containers can burst violently or explode

when heated, due to excessive pressure build-up. Static electricity and formation of sparks

must be prevented.

Materials to avoid Oxidizing materials. Acids - oxidizing.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD50) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable

as to its carcinogenicity to humans.

CDI - STENCIL, SQUEEGEE and MISPRINT CLEANER, BULK

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

Based on available data the classification criteria are not met.

development

Specific target organ toxicity - single exposure

STOT - single exposureNot classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure
Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation No specific symptoms known.

Ingestion May cause irritation.

Skin contact Redness. Irritating to skin.

Eye contact Irritating to eyes.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

Toxicological information on ingredients

PROPAN-2-OL

Carcinogenicity

IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed.

12. Ecological information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

Toxicity Based on available data the classification criteria are not met.

Ecological information on ingredients

PROPAN-2-OL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 9,640 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 5102 mg/l, Daphnia magna

Acute toxicity - aquatic

IC₅₀, 72 hours: >2,000 mg/l, Algae

plants

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients

PROPAN-2-OL

Partition coefficient : 0.05

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product

residues and hence be potentially hazardous.

Disposal methodsDo not empty into drains. Dispose of surplus products and those that cannot be recycled via a

licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is

not feasible.

14. Transport information

UN number

UN No. (TDG) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

UN proper shipping name

Proper shipping name (TDG) FLAMMABLE LIQUID, N.O.S. (CONTAINS Glycol Ethers, Isopropanol)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S. (CONTAINS 1-propoxypropan-2-ol, ETHYL ACETATE)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (CONTAINS 1-propoxypropan-2-ol, ETHYL ACETATE)

Proper shipping name (DOT) UN1993, FLAMMABLE LIQUID, N.O.S. (Glycol Ethers, Isopropanol), 3, PGIII

Transport hazard class(es)

DOT class 3

TDG class 3

TDG label(s) 3

IMDG class 3

ICAO class/division 3

Transport labels



Packing group

TDG packing group III
IMDG packing group III
ICAO packing group III
DOT packing group III

Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

Special precautions for user

EmS F-E, S-E

Transport in bulk according to Not relevant.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

Inventories

Canada - DSL/NDSL

The following ingredients are listed or exempt:

1-propoxypropan-2-ol

ETHYL ACETATE

PROPAN-2-OL

16. Other information

Classification abbreviations Flam. Liq. = Flammable liquid

and acronyms Eye Irrit. = Eye irritation

Skin Irrit. = Skin irritation

Training advice Only trained personnel should use this material.

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 2021-06-03

Revision 28

Supersedes date 2018-08-01

SDS number BULK - CDI

SDS status Approved.

Hazard statements in full H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.