



## MATERIAL SAFETY DATA SHEET AXL - AXAREL 2200 AEROSOL

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**PRODUCT NAME** AXL - AXAREL 2200 AEROSOL  
**PRODUCT NO.** MCC-AXL, MCC-AXL101, MCC-DAXL, MCC-NAXL  
**PRODUCT USE** Cleaning agent.  
**SUPPLIER** MICROCARE CORPORATION  
595 John Downey Drive  
New Britain, CT 06051  
United States of America  
CAGE: OATV9  
+1 860-827-0626  
+1 860-827-8105  
techsupport@microcare.com  
**EMERGENCY TELEPHONE** CHEMTREC (800) 424-9300  
**IDENTIFICATION No.** UN1950

### 2 HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

FLAMMABLE. Colourless liquid. Prolonged or repeated contact leads to drying of skin. The liquid may irritate the skin, the eyes and the respiratory tract. Vapors are heavier than air and may travel along the floor and in the bottom of containers. Vapors may be ignited by a spark, a hot surface or an ember. No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation. Keep out of the reach of children.

#### POTENTIAL HEALTH EFFECTS

##### INHALATION

May cause irritation to the respiratory system. Vapors may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. High concentrations of vapors may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

##### INGESTION

Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. May cause nausea, headache, dizziness and intoxication. Unconsciousness.

##### SKIN CONTACT

Product has a defatting effect on skin. May cause skin irritation/eczema.

##### EYE CONTACT

Irritating to eyes.

##### CARCINOGENICITY

This substance has no evidence of carcinogenic properties.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %
1-propoxypropan-2-ol	216-372-4	1569-01-3	30-60%
HFC-134a Tetrafluoroethane	212-377-0	811-97-2	10-30%
MIXED ALIPAHTIC HYDROCARBONS		90622-57-4	30-60%

### 4 FIRST-AID MEASURES

#### GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

## AXL - AXAREL 2200 AEROSOL

### INHALATION

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

### INGESTION

DO NOT INDUCE VOMITING! Immediately rinse mouth and drink plenty of water (200-300 ml). Do not give victim anything to drink if he is unconscious. Consult a physician for specific advice.

### SKIN CONTACT

Promptly wash contaminated skin with water. Promptly remove clothing if soaked through and wash the skin with water. Contact physician if irritation continues.

### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## 5 FIRE-FIGHTING MEASURES

### EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

### SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapors.

### UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

### SPECIFIC HAZARDS

The product is flammable, and heating may generate vapors which may form explosive vapor/air mixtures. In case of fire, toxic gases may be formed.

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire. Face mask, protective gloves and safety helmet.

**FLAMMABILITY LIMIT - LOWER(%)** 2.0

**FLAMMABILITY LIMIT - UPPER(%)** 12.7

**FLASH POINT (°C)** 44 C / 111 F TCC (Tag closed cup).

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear approved, tight fitting safety glasses where splashing is probable.

### ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

### SPILL CLEAN UP METHODS

Wear necessary protective equipment. If leakage cannot be stopped, evacuate area. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

## 7 HANDLING AND STORAGE

### HANDLING

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Keep out of the reach of children.

### STORAGE

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

### PROTECTIVE EQUIPMENT

## AXL - AXAREL 2200 AEROSOL



### ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit

### HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves. Gloves of nitrile rubber, PVA or Viton are recommended.

### EYE PROTECTION

Use eye protection. Wear approved, tight fitting safety glasses where splashing is probable.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOR	Clear Colourless.
ODOR	Odor of alcohol. Ester.
PHYSICAL DATA COMMENTS	Aerosol.
VOLATILITY DESCRIPTION	Volatile
SOLUBILITY	Soluble in water.
BOILING POINT (°C)	149-193 C / 300-380 F
VAPOR DENSITY (air=1)	5.0
VAPOR PRESSURE	2.0 mm Hg 20 C / 68 F
VOLATILE BY VOL. (%)	100
FLASH POINT (°C)	44 C / 111 F TCC (Tag closed cup).
SOLUBILITY VALUE (g/100g H <sub>2</sub> O@20°C)	60
VOLATILE ORGANIC CONTENT	785 g/litre

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions.

### CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidizing agents. Strong alkalis. Strong mineral acids.

### HAZARDOUS POLYMERISATION

Will not polymerise.

### MATERIALS TO AVOID

Strong oxidizing substances.

### HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapors/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## 11 TOXICOLOGICAL INFORMATION

Name	HFC-134a Tetrafluoroethane
Toxic Dose 1 - LD 50	>2085 mg/kg (oral rat)
Other Health Effects	This substance has no evidence of carcinogenic properties.

## AXL - AXAREL 2200 AEROSOL

**Name** 1-propoxypropan-2-ol  
**Toxic Dose 1 - LD 50** 3550 mg/kg (oral-rbt)  
**Name** MIXED ALIPAHTIC HYDROCARBONS

### 12 ECOLOGICAL INFORMATION

#### MOBILITY

Considering the limited amount applied during use and the size of the container, the risk of adverse effects is considered small.

**Name** HFC-134a Tetrafluoroethane  
**LC 50, 96 Hrs, Fish mg/l** 450  
**EC 50, 48 Hrs, Daphnia, mg/l** 980  
**Name** 1-propoxypropan-2-ol  
 MIXED ALIPAHTIC HYDROCARBONS

### 13 DISPOSAL CONSIDERATIONS

#### DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Recover and reclaim or recycle, if practical. Dispose of waste and residues in accordance with local authority requirements.

### 14 TRANSPORT INFORMATION



**DOT PROPER SHIPPING NAME** AEROSOLS  
**DOT PROPER SHIPPING NAME** Consumer Commodity ORM-D  
**TDG SHIPPING NAME** AEROSOLS  
**IDENTIFICATION No.** UN1950  
**UN NO. SEA** 1950  
**IMDG CLASS** 2.1  
**IMDG PAGE NO.** 94  
**IMDG PACK GR.** N/A  
**EMS** F-D, S-U  
**MFAG** See Subsection 4.2 of MFAG.  
**UN NO. AIR** 1950  
**AIR CLASS** 2.1  
**AIR SUB CLASS** N/A  
**AIR PACK GR.** N/A

### 15 REGULATORY INFORMATION

#### INVENTORIES

COMPONENT	CAN	US	EU	AUS	JAP	KOR	CHN	PHLP
HFC-134a Tetrafluoroethane	DSL	Yes.						

COMPONENT	TSCA 12(b) Export Notification
HFC-134a Tetrafluoroethane	No.

#### SARA (311/312) HAZARD CATEGORIES

Acute Chronic Fire

## AXL - AXAREL 2200 AEROSOL

### REGULATORY STATUS (US)

This Product is Hazardous under the OSHA Hazard Communication Standard. TSCA: The ingredients of this product are on the TSCA Inventory.

### REGULATORY REFERENCES

NFPA30 Flammable and Combustible Liquids Code. 29 CFR 1910.1010 Federal Regulations (OSHA Standard).

### WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM -WHMIS

#### LABEL(S) FOR SUPPLY



Compressed Gas.



Flammable Aerosol.



Materials Causing Other Toxic Effects.

### CONTROLLED PRODUCT CLASSIFICATION


Canadian WHMIS Classification A B5 D2A WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (CPR SECTION (33)) This product has been classified according to the hazard criteria of the Controlled Product Regulations, and the MSDS contains all required information.

### 16 OTHER INFORMATION

### HAZARDOUS MATERIAL INFORMATION SYSTEM (HMIS)

HEALTH	1
FLAMMABILITY	2
PHYSICAL	0
PERSONAL PROTECTION	N/A.

### NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)



### REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

REVISION DATE 14/07/2009

VERSION No. 1

### SAFETY DATA SHEET STATUS

Approved.

DATE January 7, 2011

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his o