



SAFETY DATA SHEET

UFR UNIVERSAL FLUX REMOVER, AEROSOL

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name UFR UNIVERSAL FLUX REMOVER, AEROSOL
Product number MCC-UFR107

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Supplier MICROCARE EUROPE BVBA
 VEKESTRAAT 29 B11
 INDUSTRIEZONE 'T SAS
 1910 KAMPENHOUT, Belgium
 Phone +32.2.251.95.05
 Fax +32.2.400.96.39
 EuroSales@microcare.com

Manufacturer MICROCARE U.K. LTD
 SEVEN HILLS BUSINESS CENTRE
 SOUTH STREET, MORLEY
 LEEDS, WEST YORKSHIRE, UK LS27 8AT
 Tel: +44 (0) 113 3609019
 mcceurope@microcare.com

1.4. Emergency telephone number

Emergency telephone INFOTRAC +44 330 027 0156 (UK)
 1-352-323-3500 (from anywhere in the world)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Aquatic Chronic 3 - H412

Human health Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Mild dermatitis, allergic skin rash.

Environmental The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Not considered to be a significant hazard due to the small quantities used. Gas or vapour displaces oxygen available for breathing (asphyxiant).

UFR UNIVERSAL FLUX REMOVER, AEROSOL

2.2. Label elements

Hazard statements	H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	Safety data sheet available on request. For use in industrial installations only.
Supplementary precautionary statements	P273 Avoid release to the environment.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

trans-1-Chloro-3,3,3-trifluoropropene	60-100%
CAS number: 102687-65-0	
Classification Press. Gas (Liq.) - H280 Aquatic Chronic 3 - H412	
TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE	10-30%
CAS number: 29118-24-9	EC number: 471-480-0
	REACH registration number: 01-0000019758-54-0000
Classification Press. Gas (Liq.) - H280	
ETHANOL	1-5%
CAS number: 64-17-5	EC number: 200-578-6
Classification Flam. Liq. 2 - H225	
METHANOL	<1%
CAS number: 67-56-1	EC number: 200-659-6
Classification Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370	

UFR UNIVERSAL FLUX REMOVER, AEROSOL

4-methylpentan-2-one	<1%
CAS number: 108-10-1	EC number: 203-550-1
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H332	
Eye Irrit. 2 - H319	
STOT SE 3 - H335	
ethyl acetate	<1%
CAS number: 141-78-6	EC number: 205-500-4
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	

The full text for all hazard statements is displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

Composition

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Never give anything by mouth to an unconscious person. Do not induce vomiting. Place unconscious person on the side in the recovery position and ensure breathing can take place. If breathing stops, provide artificial respiration. Consult a physician for specific advice.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
Ingestion	Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. Get medical attention.
Skin contact	Remove contaminated clothing and rinse skin thoroughly with water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Consult a physician for specific advice.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Get medical attention promptly if symptoms occur after washing.
Inhalation	Upper respiratory irritation. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Gas or vapour displaces oxygen available for breathing (asphyxiant). Une inhalation prolongée ou excessive peut irriter les voies respiratoires.
Ingestion	May cause stomach pain or vomiting. Diarrhoea. May cause nausea, headache, dizziness and intoxication. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Skin contact Skin irritation. This product is rapidly absorbed through the skin and may cause symptoms similar to those of ingestion.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours. Aerosol containers can explode when heated, due to excessive pressure build-up.

Hazardous combustion products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Fire or high temperatures create: Carbonyl compounds. Mineral acids.

5.3. Advice for firefighters

Protective actions during firefighting Move containers from fire area if it can be done without risk. Bursting aerosol containers may be propelled from a fire at high speed.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

6.2. Environmental precautions

Environmental precautions Contain spillage with sand, earth or other suitable non-combustible material. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Usage precautions Provide adequate ventilation. Avoid inhalation of vapours/spray and contact with skin and eyes. Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours. Keep out of the reach of children.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Reference to other sections. Store away from incompatible materials (see Section 10).

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

trans-1-Chloro-3,3,3-trifluoropropene

Long-term exposure limit (8-hour TWA): 800 ppm

ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

METHANOL

Long-term exposure limit (8-hour TWA): WEL 200 ppm 266 mg/m³

Short-term exposure limit (15-minute): WEL 250 ppm 333 mg/m³

Sk

4-methylpentan-2-one

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

Sk

ethyl acetate

Long-term exposure limit (8-hour TWA): WEL 200 ppm

Short-term exposure limit (15-minute): WEL 400 ppm

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

Ingredient comments OES = Occupational Exposure Standard. SUP = Supplier's recommendation.

trans-1-Chloro-3,3,3-trifluoropropene (CAS: 102687-65-0)

Ingredient comments No exposure limits known for ingredient(s).

DNEL Workers - Inhalation; Long term systemic effects: 1779 mg/m³

DMEL Consumer - Inhalation; Long term systemic effects: 379 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

No specific ventilation requirements. This product must not be handled in a confined space without adequate ventilation.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber).
Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination. Wear apron or protective clothing in case of contact.
Hygiene measures	No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products. When using do not eat, drink or smoke.
Respiratory protection	Considering the size of the packaging, the risk is regarded as minimal. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Wear self-contained breathing apparatus with full facepiece.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol. Liquid. Gas
Colour	Clear liquid. Colourless.
Odour	Slight.
Odour threshold	No information available.
pH	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	19°C/66°F @ 101.3 kPa
Flash point	Not applicable. The product is not flammable.
Evaporation rate	Not determined.
Evaporation factor	No information available.
Upper/lower flammability or explosive limits	Not applicable.
Other flammability	No information available.
Vapour pressure	1.91 kPa @ 20°C
Vapour density	>1
Relative density	1.24
Bulk density	No information available.
Solubility(ies)	Slightly soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Global Warming Potential (GWP)

Surface tension

9.2. Other information

Refractive index	No information available.
Particle size	No information available.
Molecular weight	No information available.
Volatility	100%
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	This product contains a maximum VOC content of 59 g/litre.
Heat of vaporization (at boiling point), cal/g (Btu/lb)	

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.

10.5. Incompatible materials

Materials to avoid Alkali metals. Alkaline earth metals.

10.6. Hazardous decomposition products

Hazardous decomposition products Heating may generate the following products: Toxic and corrosive gases or vapours. Halogenated hydrocarbons. Hydrogen fluoride (HF). Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - oral

ATE oral (mg/kg) 50,384.18

Acute toxicity - dermal

ATE dermal (mg/kg) 151,152.54

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 1,511.53

UFR UNIVERSAL FLUX REMOVER, AEROSOL

ATE inhalation (dusts/mists mg/l) 251.92

Inhalation	Vapours may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing.
Ingestion	May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.
Skin contact	Product has a defatting effect on skin. May cause allergic contact eczema.
Eye contact	May cause temporary eye irritation.
Medical symptoms	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

Toxicological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Acute toxicity - oral

Notes (oral LD₅₀) No information available.

Acute toxicity - dermal

Notes (dermal LD₅₀) No information required.

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV) 120,000.0

Species Rat

ATE inhalation (gases ppm) 120,000.0

Inhalation	Vapours may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing.
Ingestion	May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.
Skin contact	Product has a defatting effect on skin. May cause allergic contact eczema.
Eye contact	May cause temporary eye irritation.
Medical symptoms	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 965.0

Species Rat

ATE inhalation (vapours mg/l) 965.0

UFR UNIVERSAL FLUX REMOVER, AEROSOL

ETHANOL

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 20,000.0

ATE inhalation (vapours mg/l) 20,000.0

METHANOL

Acute toxicity - oral

Notes (oral LD₅₀) Acute Tox. 3 - H301 Toxic if swallowed.

ATE oral (mg/kg) 100.0

Acute toxicity - dermal

Notes (dermal LD₅₀) Acute Tox. 3 - H311 Toxic in contact with skin.

ATE dermal (mg/kg) 300.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Acute Tox. 3 - H331 Toxic if inhaled.

ATE inhalation (vapours mg/l) 3.0

ATE inhalation (dusts/mists mg/l) 0.5

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 1 - H370 Causes damage to organs .

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo. Unconsciousness. High concentrations may be fatal.

Ingestion

May cause stomach pain or vomiting. May cause severe internal injury.

Skin contact

A single exposure may cause the following adverse effects: Pain.

Eye contact

No specific symptoms known.

Route of exposure

Ingestion Inhalation Skin and/or eye contact

Target organs

No specific target organs known.

4-methylpentan-2-one

Carcinogenicity

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

SECTION 12: Ecological information

Ecotoxicity There are no data on the ecotoxicity of this product.

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Ecotoxicity

The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

METHANOL

Ecotoxicity

Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Acute aquatic toxicity

Acute toxicity - fish

, : , Oncorhynchus mykiss (Rainbow trout)
LC₅₀, 96 hours: 38 mg/l mg/l, Fish

Acute toxicity - aquatic invertebrates

EC₅₀, 48 hours: 82 mg/l, Freshwater invertebrates

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Acute toxicity - aquatic plants EC₅₀, 72 hours: 106.7 mg/l, Freshwater algae
NOEC, 72 hours: 115 mg/l, Freshwater algae

TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE

Acute aquatic toxicity

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >160 mg/l, Daphnia magna

ETHANOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >10,000 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 7,800 mg/l, Daphnia magna

Acute toxicity - aquatic plants , 96 hours: 1000 mg/l, Freshwater algae

METHANOL

Toxicity Based on available data the classification criteria are not met.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >100 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >10000 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Persistence and degradability The product is not readily biodegradable.

TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE

Persistence and degradability The product is not readily biodegradable.

ETHANOL

Persistence and degradability The product is expected to be biodegradable.

METHANOL

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Partition coefficient No information available.

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Kow: 2.09

ETHANOL

Bioaccumulative potential Bioaccumulation is unlikely.

Partition coefficient No information available.

METHANOL

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient : -0.77

12.4. Mobility in soil

Mobility The product contains volatile substances which may spread in the atmosphere.

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Mobility No data available.

ETHANOL

Mobility The product is soluble in water.

METHANOL

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB. No data available.

12.6. Other adverse effects

Other adverse effects The product contains a substance which has a photochemical ozone creation potential.

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Other adverse effects None known.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

METHANOL

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Empty containers must not be punctured or incinerated because of the risk of an explosion. Aerosol containers can explode when heated, due to excessive pressure build-up. Reuse or recycle products wherever possible.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.2
ADR/RID classification code	5A,5O
ADR/RID label	2.2
IMDG class	2.2
ICAO class/division	2.2
ADN class	2.2

Transport labels



14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ICAO packing group	None
ADN packing group	None

UFR UNIVERSAL FLUX REMOVER, AEROSOL

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 3

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance Workplace Exposure Limits EH40.
Introduction to Local Exhaust Ventilation HS(G)37.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

US - TSCA

Yes

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 01/06/2021

Revision 43

Supersedes date 21/05/2021

SDS number AEROSOL - UFR107

SDS status Approved.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Hazard statements in full

H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H370 Causes damage to organs .
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.