

SAFETY DATA SHEET

DGF14A - Duraglide Dry Lubricant, Aerosol

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

1. Identification

Product identifier

Product name DGF14A - Duraglide Dry Lubricant, Aerosol

Product number MCC-DGF14A

Recommended use of the chemical and restrictions on use

Restriction on use Lubricant.

Uses advised againstNo specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier MICROCARE LLC

Manufacturer MICROCARE LLC

595 John Downey Drive New Britain, CT 06051 United States of America

CAGE: OATV9

Tel: +1 800-638-0125, +1 860-827-0626

techsupport@microcare.com

Emergency telephone number

Emergency telephone INFOTRAC 1-800-535-5053 (CANADA and U.S.A.)

1-352-323-3500 (from anywhere in the world)

2. Hazard identification

Classification of the substance or mixture

WHMIS Regulatory Status This product has been classified according to the hazard criteria of the Hazardous Product

Regulations and the SDS contains all required information.

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Label elements

Hazard statements NC Not Classified

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with local regulations.

DGF14A - Duraglide Dry Lubricant, Aerosol

Supplemental label

Safety data sheet available on request. For use in industrial installations only.

information

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

HFC-134a Tetrafluoroethane 60-100%

CAS number: 811-97-2

Classification

Press. Gas, Liquefied - H280 Simple Asphyxiants - Category 1

PROPAN-2-OL 1-5% Trade secret

CAS number: 67-63-0

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

Poly-tfe, omega-hydro-alpha-(methylcyclohexyl)

<1%

CAS number: 65530-85-0

Classification
Not Classified

The full text for all hazard statements is displayed in Section 16.

Composition comments Not applicable.

Composition

4. First-aid measures

Description of first aid measures

personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms

are severe or persist.

Ingestion Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not

induce vomiting unless under the direction of medical personnel.

Skin contact Rinse with water.

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical

attention if any discomfort continues.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

DGF14A - Duraglide Dry Lubricant, Aerosol

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Spray/mists may cause respiratory tract irritation.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact

Repeated exposure may cause skin dryness or cracking.

Eye contact

May be slightly irritating to eyes. May cause discomfort.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the hazardous product

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and

propellant.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapours.

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs,

notify appropriate authorities.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial

guidelines on occupational health and safety or by NFPA standards if applicable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be

taken without appropriate training or involving any personal risk. Do not touch or walk into

spilled material. Evacuate area. Risk of explosion.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

DGF14A - Duraglide Dry Lubricant, Aerosol

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store away from incompatible materials (see Section 10). Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F.

Storage class Chemical storage.

Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

Usage description Lubricant.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

HFC-134a Tetrafluoroethane

Long-term exposure limit (8-hour TWA): OES 4240 mg/m³

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³ Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³ A4

ACGIH = American Conference of Governmental Industrial Hygienists. A4 = Not Classifiable as a Human Carcinogen.

Ingredient comments WEL = Workplace Exposure Limits

DGF14A - Duraglide Dry Lubricant, Aerosol

Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or

ingredients.

Eye/face protectionUnless the assessment indicates a higher degree of protection is required, the following

protection should be worn: Tight-fitting safety glasses.

Hand protection No specific hand protection recommended.

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke

when using this product.

Respiratory protection Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH

approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Full face mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial

regulation relating to health and safety at work.

Environmental exposure

controls

Keep container tightly sealed when not in use.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Liquid. Aerosol.

Colour White/off-white. Waxy solid.

Odour Slight alcoholic.

Odour threshold Not determined.

Melting point PTFE Content only 300°C/581°F

Initial boiling point and range -26.5°C/-15.7°F @ 101.3 kPa

Flash point No information available.

Evaporation rate No information available.

Evaporation factor No information available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Not determined.

Other flammability The product is not flammable.

Vapour pressure 663 kPa @ 25°C

DGF14A - Duraglide Dry Lubricant, Aerosol

Vapour density 3.18 @ 25 (C) / 77 (F)

Relative density No information available.

Bulk density No information available.

Solubility(ies) Slightly soluble in water.

Partition coefficient No information available.

Decomposition Temperature No information available.

Explosive properties No information available.

Comments Aerosol.

Global Warming Potential

(GWP)

Surface tension

Particle size 1-15 micron

Volatility 98.5%

Volatile organic compound No information available.

Heat of vaporization (at boiling

point), cal/g (Btu/lb)

10. Stability and reactivity

Reactivity See the other subsections of this section for further details.

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Possibility of hazardous

reactions

No potentially hazardous reactions known.

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurized

container: may burst if heated

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀)

Based on available data the classification criteria are not met.

Skin corrosion/irritation

DGF14A - Duraglide Dry Lubricant, Aerosol

Animal data

Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable

as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure
Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Spray/mists may cause respiratory tract irritation.

Ingestion Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May be slightly irritating to eyes. May cause discomfort.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

Toxicological information on ingredients

HFC-134a Tetrafluoroethane

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - inhalation

Acute toxicity inhalation 567,000.0

(LC₅₀ gases ppmV)

DGF14A - Duraglide Dry Lubricant, Aerosol

Species Rat

ATE inhalation (gases

ppmV)

567,000.0

.

Inhalation Vapours irritate the respiratory system. May cause coughing and difficulties in

breathing.

Ingestion May cause stomach pain or vomiting. May cause nausea, headache, dizziness and

intoxication.

Skin contact May cause allergic contact eczema. Contact with liquid form may cause frostbite.

Eye contact May cause temporary eye irritation.

PROPAN-2-OL

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed.

12. Ecological information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

Toxicity Based on available data the classification criteria are not met.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 450 mg/L mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 980 mg/L mg/l, Daphnia magna

Ecological information on ingredients

HFC-134a Tetrafluoroethane

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 450 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 980 mg/l, Daphnia magna

PROPAN-2-OL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 9,640 mg/l, Fish

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 5102 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

IC₅₀, 72 hours: >2,000 mg/l, Algae

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

DGF14A - Duraglide Dry Lubricant, Aerosol

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients

HFC-134a Tetrafluoroethane

Partition coefficient Pow: 1.06

PROPAN-2-OL

Partition coefficient : 0.05

Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product

residues and hence be potentially hazardous.

Disposal methods Do not empty into drains. Empty containers must not be punctured or incinerated because of

the risk of an explosion. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers,

labeled with their contents.

14. Transport information

UN number

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN proper shipping name

Proper shipping name (TDG) LIMITED QUANTITY

Proper shipping name (IMDG) UN1950, Aerosols, Non-Flammable, 2.2, Limited Quantity

Proper shipping name (ICAO) UN1950, Aerosols, Non-Flammable, 2.2, Limited Quantity

Proper shipping name (DOT) LIMITED QUANTITY

Special precautions for user

Not applicable.

DGF14A - Duraglide Dry Lubricant, Aerosol

Transport in bulk according to Not relevant. No information required. **Annex II of MARPOL 73/78** and the IBC Code

15. Regulatory information

Guidance Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

16. Other information

Classification abbreviations

and acronyms

Aerosol = Aerosol

Training advice Only trained personnel should use this material.

Revision date 2021-06-03

Revision 33

Supersedes date 2020-09-09

SDS number AEROSOL - DGF14A

SDS status Approved.

Hazard statements in full H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

May displace oxygen and cause rapid suffocation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.