



SAFETY DATA SHEET

Stereze 70% Isopropyl Alcohol, Pump Spray

According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR)

1. Identification

Product identifier

Product name Stereze 70% Isopropyl Alcohol, Pump Spray
Chemical name 70% Isopropyl Alcohol
Product number STIA32PS

Recommended use of the chemical and restrictions on use

Restriction on use Cleaning agent.
Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier MICROCARE LLC
595 John Downey Drive
New Britain, CT 06051
United States of America
CAGE: OATV9
Tel: +1 860-827-0626
Fax: +1 860-827-8105
techsupport@microcare.com

Manufacturer MICROCARE LLC
595 John Downey Drive
New Britain, CT 06051
United States of America
CAGE: OATV9
Tel: +1 800-638-0125, +1 860-827-0626
Fax: +1 860-827-8105
techsupport@microcare.com

Emergency telephone number

Emergency telephone CHEMTREC 1-800-424-9300 (within the U.S.)
+1 703-741-5970 (from anywhere in the world)

2. Hazard identification

Classification of the substance or mixture

Physical hazards Flam. Liq. 2 - H225
Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336
Environmental hazards Not Classified

Label elements

Stereze 70% Isopropyl Alcohol, Pump Spray

Hazard pictograms



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapour/ spray.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/ attention.
P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

Contains

PROPAN-2-OL

3. Composition/information on ingredients

Mixtures

PROPAN-2-OL	60-100%
CAS number: 67-63-0	
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	

The full text for all hazard statements is displayed in Section 16.

Composition

4. First-aid measures

Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical attention if symptoms are severe or persist.
Eye contact	Rinse with water. Do not rub eye. Remove any contact lenses and open eyelids wide apart. Get medical attention if any discomfort continues.

Most important symptoms and effects, both acute and delayed

Stereze 70% Isopropyl Alcohol, Pump Spray

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	Irritating to eyes.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the hazardous product

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of vapours and spray/mists. Use suitable respiratory protection if ventilation is inadequate.

Environmental precautions

Stereze 70% Isopropyl Alcohol, Pump Spray

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. The contaminated absorbent may pose the same hazard as the spilled material. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Keep away from food, drink and animal feeding stuffs. Keep container tightly sealed when not in use. The product is flammable.

Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

Storage class Flammable liquid storage.

Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

Reference to other sections. Store away from incompatible materials (see Section 10).

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³

Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³

A4

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

Exposure controls

Hand protection No specific hand protection recommended.

Environmental exposure controls Keep container tightly sealed when not in use.

9. Physical and chemical properties

Stereze 70% Isopropyl Alcohol, Pump Spray

Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Colourless.
Odour	Alcoholic.
Odour threshold	No information available.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	82°C/180°F @ 101.3 kPa
Flash point	12°C/53°F Tag closed cup.
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 2.0 %(V) Upper flammable/explosive limit: 12.7 %(V)
Other flammability	No information available.
Vapour pressure	5.2 kPa @ 20°C
Vapour density	1.82
Relative density	0.87
Bulk density	No information available.
Solubility(ies)	Soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Global Warming Potential (GWP)	
Refractive index	No information available.
Particle size	Not applicable.
Molecular weight	Not applicable.
Volatility	100%
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	This product contains a maximum VOC content of 350 g/l. This product contains a maximum VOC content of 70 %.

10. Stability and reactivity

Stereze 70% Isopropyl Alcohol, Pump Spray

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	The following materials may react strongly with the product: Oxidizing agents.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.
Materials to avoid	Oxidizing materials. Acids - oxidizing.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

11. Toxicological information

12. Ecological information

Bioaccumulative potential

Partition coefficient No information available.

13. Disposal considerations

Waste treatment methods

General information	The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

14. Transport information

UN number

UN No. (TDG)	UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL), 3, PGII, LIMITED QUANTITY
UN No. (IMDG)	UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL), 3, PGII, LIMITED QUANTITY
UN No. (ICAO)	UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL), 3, PGII, LIMITED QUANTITY
UN No. (DOT)	UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL), 3, PGII, LIMITED QUANTITY

UN proper shipping name

Proper shipping name (IMDG)	UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL), 3, PGII, LIMITED QUANTITY
Proper shipping name (ICAO)	UN1993, FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL), 3, PGII, LIMITED QUANTITY

Environmental hazards

Stereze 70% Isopropyl Alcohol, Pump Spray

Environmentally hazardous substance/marine pollutant

No.

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78
and the IBC Code**

15. Regulatory information

Inventories

Canada – DSL/NDSL

DSL

US - TSCA

Present.

US – TSCA 12(b) Export Notification

Not listed.

16. Other information

Revision date	2020-11-24
Revision	9
Supersedes date	2020-11-24
SDS number	BULK - STIA32PS
Hazard statements in full	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.