

MicroCare™
ENGINEERED FLUIDS

HFE7200

Cleaning & Rinsing Agent, Carrier Fluid

Use for electronics cleaning and lubricant deposition

- Ideal replacement for 3M™ Novec™ 7200 Engineered Fluid
- Effective replacement for CFC, HCFC, HFC and PFC fluids, enabling greener operations

Introduction

MicroCare™ HFE7200 Engineered Fluid is a clear, colorless, and low odor vapor degreasing fluid designed for various applications, including parts cleaning, rinsing, heat transferring for sensitive processes and carrying and deposition of lubricants and coatings. Its low surface tension and low viscosity make it ideal for light-duty vapor degreasing or cold cleaning applications.

Benefits

- Non-flammable for improved workplace safety
- Very low global warming potential (GWP), contributing to climate protection
- Non-ozone depleting, ensuring minimal environmental impact
- Fast drying for improved process efficiency
- Excellent toxicity profile (200 ppm)
- Provides reliable chemical and thermal stability

Use Procedures

It is recommended that MicroCare™ HFE7200 Engineered Fluid be used in a vapor degreaser or closed-loop system to maximize cleaning efficiency, economy, and emission control. Cleaning procedures for MicroCare™ HFE7200 are like those of conventional vapor degreasing products. The procedures consist of immersing a workload into the vapor or boiling solvent, rinsing with solvent, and then drying in the solvent vapor. Coating can be conducted by mixing the coating material with MicroCare™ HFE7200 Engineered Fluid and dipping a workload into the coating bath followed by air drying.

Recovery

MicroCare™ HFE7200 Engineered Fluid is recoverable by simple distillation, either by using a vapor degreaser or a simple still apparatus, reducing waste and operational costs. Recovery should be closely watched to ensure that the operating levels are maintained. Spent ingredients and still bottoms need to be disposed of according to Federal, State and local regulations.



Replacements for
3M™ Novec™
Engineered Fluids

We offer chemically equivalent fluid formulas for the ones you already rely on, delivering the same high-quality cleaning performance without costly operational changes.

Our products meet or exceed 3M Novec™ performance standards, and as a leading supplier of high-purity HFEs, we ensure they pass the industry's most stringent quality metrics.

MicroCare™
ENGINEERED FLUIDS

Applications

- Removing light oils and particulates
- Lubricant carrier for fluorocarbons, hydrocarbons and silicones

Specifications

Table 1. Physical Properties

Formula	$C_4F_9OC_2H_5$
Molecular Weight	264
Boiling Point (°C)	76
Freeze Point (°C)	-138
Liquid Density (g/ml)	1.43
Surface Tension (dynes/cm)	13.6
Solubility of Solvent in Water (ppmw)	<20
Solubility of Water in Solvent (ppmw)	92
Vapor Pressure (mmHg)	109
Viscosity (cps)	0.61
Heat of Vaporization (cal/g @ boiling point)	30
Specific Heat (cal/g°C)	0.29

Table 2. Product Comparison Chart

Property	MicroCare™ HFE7200	Opteon™ SF33	Vertrel™ XF	Tergo™ PF100	Teres™
BP (C)	76	33	55	56	51
KB value	<20	<20	<20	<20	<20
Specific Gravity	1.53	1.36	1.58	1.47	1.39
Surface Tension (dyne/cm)	13.6	13	14.1	16.4	15
GWP	55	2	1650	580	27
Plastic Compatibility	Good	Good	Good	Good	Fair

Materials Compatibility

MicroCare™ HFE7200 Engineered Fluid is compatible with most metals and hard polymers such as:

Short-Term Exposure Compatibility		
Metals	Plastics	Elastomers
Aluminum	Acrylic (PMMA)	Butyl Rubber
Molybdenum	Epoxy	Natural Rubber
Copper	Polyethylene	Nitrile Rubber
Tantalum	PET	EPDM
Carbon Steel	Polypropylene	
Tungsten	Phenolic	
302 Stainless Steel	Polycarbonate	
Cu/Be Alloy C172	ABS	
Brass	Polyester	
Mg Alloy AZ32B		

Exceptions: Some swelling of PTFE and Silicone Rubber. Some surface oxidation of copper during heat aging.

Environmental Health and Safety

Ozone Depletion Potential (ODP) ¹	None
Global Warming Potential (GWP) ²	55
Atmospheric Lifetime (years)	0.77
Flash Point	None
Flammability Range in Air	2.4–12.4%
Exposure Guidelines (8 hr. time-weighted average)	200
Acute Toxicity (4 hr. LC ₅₀ [Rat])	>92,000

¹ HCFC-225 ca/cb ratio is 45/55

² CFC-11 = 1.0

Storage and Handling

Before using this product, carefully read and follow all precautions and directions provided on the product label and in the Safety Data Sheet (SDS).

MicroCare™ HFE7200 Engineered Fluid is nonflammable and highly resistant to thermal breakdown and hydrolysis during storage and use. It is thermally and hydrolytically stable, keeping integrity under normal storage conditions without oxidation or degradation. To ensure the best performance, store containers in a clean, dry area away from direct sunlight, with a recommended storage temperature not exceeding 30°C.

For detailed handling and safety recommendations, refer to the SDS, available from your local representative or online at microcare.com.



The information set forth herein is based on data believed to be reliable. MicroCare makes no warranties express or implied as to its accuracy and assumes no liability arising out of its use by others. This publication is not to be taken as a license to operate under, nor infringe upon, any patents not herein expressly described.



MicroCare.com



Follow Us!

MicroCare, LLC

595 John Downey Drive
New Britain, CT 06051 USA
Tel: +1 860 827 0626
Toll Free: 1 800 638 0125
Email: TechSupport@MicroCare.com

MicroCare U.K. Ltd

Unit 4, Whitehall Court
Leeds
LS12 5SN UK
Tel: +44 (0) 113 3609019
Email: MCCEurope@MicroCare.com

MicroCare Asia Pte Ltd

102E, Pasir Panjang Road
Citilink, #05-06
Singapore 118529
Tel: +65 6271 0182
Email: TechSupport@MicroCare.sg



For more information
and to download SDS
visit our website:
MicroCare.com